

Orientační kurs Kč/E: 25,765

Nabídka č.: 19-03009-0
Sestava č.1.

Záruka (12-60 m.): 12
EEO (6-48 m.): 0

Polozí	Počet	Objednací číslo	Popis	Zakaznická Cena/kus €	Cena €	Ceníková Cena/kus €	Hmotnost Brutto	Rozměr obalu d x š x v	Termín vysklad. prac. dny	Dodací množství kalk. min.	Jednotka	Nahradník Produktové	Nahradník Sevisné	Následovník	Blocking	Warning	InfoText	AdditionalText	Footer	Milestone	Exportní kontrola ALNR	ECCN
10		Elektronická měřidlo S120																				
20	12	1FK2102-0AG00-1MA0	SIMOTICS S-1FK2 HD Servo motor M0=0.16 Nm, PN = 0.05 kW at nN=3000 rpm, Converter at max. 240 V supply system; Degree of protection IP64; Shaft D6x25mm with fitted key, Absolute encoder 22-bit + 12-bit multi-turn (encoder AM22DQC); with OCC interface; Connector size M12, rotatable;	279,49	3 353,94	279,49	1,66 KG	462x50x267 MM	15	1	1	ST									LF-3/7 Da N	N
30	12	6SL3210-5HB10-1UF0	SINAMICS S1210 Input voltage: 200-240V 1AC; -10%/+10%; 1.4A; 45-66Hz; Output voltage: 0 output V, 0.8 A @ 550Hz; Motor: 0.1 kW; degree of protection: IP20; Frame size A: 45 x 170 x 170 (WxHxD);	275,60	3 307,20	275,60	1,4 KG	237x174x167 MM	10	1	1	ST									LF-3/7 Da N	3A999A
40	12	6FX5002-8QN04-1AC0	Single cable prefabricated 4G0.38+2x0.38+4x0.2 C SPEED-CONNECT M12 connector Cores with end sleeve Data cable with IX connector UL/CSA DESINA MOTION-CONNECT 500 Dmax=-9.7 mm, length(m)= 0 + 0 + 2 + 0	46,73	560,72	46,73	0,404 KG	0x0x0	10	1	1	ST									LF-3/7 Da N	N
50		PLC + panel + zdroj																				
60	6	6ES7511-1TK01-0AB0	SIMATIC S7-1500T, CPU 1511T-1 PN, Central processing unit with Work memory 225 KB for program and 1 MB for data, 1st interface: PROFINET RT with 2-port switch, 60 ns bit performance, SIMATIC Memory Card required	641,07	3 846,41	641,07	0,907 KG	35,4x51,4x6,6 CM	5	1	1	ST									LF-3/7 Da N	EAR99H
70	6	6ES7954-8LE03-0AA0	SIMATIC S7 MEMORY CARD FOR S7-1500 CPUs/SINAMICS, 3.3 V FLASH, 12 MBYTE	93,48	560,85	93,48	0,03 KG	10,8x6,3x6,8 CM	5	1	1	ST									LF-3/7 Da N	N
80	6	6ES7590-1AB60-0AA0	SIMATIC S7-1500, mounting rail 160 mm (approx. 6.3 inch); incl. grounding screw, integrated DIN rail for mounting of incidentals such as terminals, automatic circuit breakers and relays	12,57	75,44	12,57	0,360 KG	21,2x6,1x2,8 CM	5	1	1	ST									LF-3/7 Da N	N
90	6	6ES7523-1BL00-0AA0	SIMATIC S7-1500 digital input/output module, DI16x 24 V DC BA, 16 channels in groups of 16, input delay type 3, 2.2ms input type 3 (IEC 61131), DQ16x24 V DC/0.5A BA; 16 channels in groups of 8; 4 A per group incl. push-in front connector	252,69	1 516,15	252,69	0,356 KG	33,3x55,1x4,5 CM	5	1	1	ST									LF-3/7 Da N	N
100	6	6AV2123-2DB03-0AX0	SIMATIC HMI, KTP400 Basic, Basic Panel, Keytouch operation, 4" TFT display, 65536 colors, PROFINET interface, configurable from WinCC Basic V13/ STEP 7 Basic V13, contains open-source software, which is provided free of charge see enclosed CD	213,05	1 278,29	213,05	0,459 KG	18,8x12,8x5,1 CM	3	1	1	ST									LF-3/7 Da N	EAR99H
110	6	6EP1333-2BA20	SITOP PSU1005 24 V/5 A Stabilized power supply input: 120/230 V AC; output: 24 V DC/5 A	61,44	368,64	61,44	0,4 KG	13x14x6 CM	3	1	1	ST							24-MONTH WARRANTY FROM DATE OF DELIVERY		LF-3/7 Da N	N
120		Koncový kabel PN																				
130	1	60K1901-1BB10-2AE0	Industrial Ethernet FastConnect RJ45 plug 180 2x 2, RJ45 plug-in connector (10/100 Mbit/s) with rugged metal enclosure and FC connection system, for IE FC cable 2x 2, 180° cable outlet 1 pack = 50 units	303,08	303,08	303,08	1,5 KG	13,7x9,3x6,3 CM	3	1	1	PAK									LF-3/7 Da N	N
140	30	6XV1870-2B	Industrial Ethernet FC TP flexible cable, GP 2x2 (PROFINET Type B), TP installation cable with flexible cores, PROFINET type B, 4-core, shielded Cat 5, sold by the meter, delivery length max. 2500 m minimum order 20 m	1,11	33,38	1,11	0,077 KG	1x1x1 MM	3	1	1	M									LF-3/7 Da N	
150		TIA portal																				
160	1	6ES7822-1BA05-4YA5	SIMATIC STEP 7 Professional V15/2017 Combo Trainer Pack; STEP 7 Professional Combo, Safety Combo, S7-PLC-SIM Advanced, OPC UA, Cloud Connector Floating License for 6 users; Software and documentation on DVD, Class A, license key on USB flash drive, 6 languages: de, en, fr, es, it, zh; executable in Windows 7 (64 bit), Windows 10 (64 bit) for configuring of SIMATIC S7-1500/1200/300/400/WinAC, SIMATIC Basic Panels; 1 x software for 20 students V15 (6ES7822-1AC05-4YA5), only for training purposes	853,43	853,43	853,43	2,344 KG	0x0x0	10	1	1	ST							FOR SCHOOLS AND TRAINING PURPOSES		LF-3/7 Da N	N
170		Prodloužení pro měřidlo (mimořádně dlouhá)																				
180	1	6SL3040-1MA01-0AA0	SINAMICS CONTROL UNIT CU320-2 PN WITHOUT COMPACT FLASH CARD	350,87	350,87	350,87	2,5 KG	226x60x30 MM	15	1	1	ST									LF-3/7 Da N	3A991X
190	1	6SL3054-0FB10-1BA0	SINAMICS S120 COMPACT FLASH CARD W/O PERFORMANCE EXTENSION INCLUDING CERTIFICATE OF LICENCE V5.1 SP1	49,55	49,55	49,55	0,012 KG	0x0x0	5	1	1	ST									LF-3/7 Da N	N
200	1	6SL3055-0AA00-2TA0	SINAMICS / SIMOTION TERMINAL BOARD TB30 FOR CONTROL UNIT CU320-2 AND SIMOTION DMS-X	209,50	209,50	209,50	0,127 KG	0x0x0	10	1	1	ST									LF-3/7 Da N	EAR99H
210	1	6SL3055-0AA00-4BA0	SINAMICS S120 BASIC OPERATOR PANEL BOP20 FOR ELECTRONIC CONTROLS TWO-LINE DISPLAY, 6 KEYS FOR PARAMETER SETTING AND DIAGNOSTIC INFORMATION SUITED FOR CONTROL UNITS CU305, CU310, CU320	21,07	21,07	21,07	0,054 KG	0x0x0	5	1	1	ST									LF-3/7 Da N	N
220	1	6SL3060-4AK00-0AA0	SINAMICS DRIVE-CLIQ CABLE (P20/P20) LENGTH 0.31 M	11,15	11,15	11,15	0,043 KG	0x0x0	10	1	1	ST									LF-3/7 Da N	N
230	2	6SL3060-4AL00-0AA0	SINAMICS DRIVE-CLIQ CABLE (P20/P20) LENGTH 0.50 M	12,55	25,10	12,55	0,06 KG	0x0x0	10	1	1	ST									LF-3/7 Da N	N
240	1	6EP1333-3BA10	SITOP PSU200M 5 A Stabilized power supply input: 120/230-500 V AC output: 24 V DC/5 A	88,75	88,75	88,75	0,6 KG	14x15x9 CM	3	1	1	ST							24-MONTH WARRANTY FROM DATE OF DELIVERY		LF-3/7 Da N	N
250	1	6SL3130-7TE23-6AA3	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60Hz OUTPUT: DC 600V, 60A, 38kW FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	1 456,99	1 456,99	1 456,99	12,4 KG	0x0x0	10	1	1	ST									LF-3/7 Da N	N
260	1	6SL3100-0BE23-6AB0	SINAMICS S120 ACTIVE INTERFACE MODULE FOR 38kW ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60Hz FRAME SIZE: BOOKSIZE	747,96	747,96	747,96	20,3 KG	0x0x0	10	1	1	ST									LF-3/7 Da N	N
270	1	6SL3120-1TE24-5AC0	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 45A FRAME SIZE: BOOKSIZE C-TYPE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLER AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	1 591,26	1 591,26	1 591,26	9,2 KG	0x0x0	10	1	1	ST									LF-3/7 Da N	3A999A
280	1	6FX5008-1BB41-1BF0	Power cable sold by the meter type: 6FX5008-1BB41 4x 6.0 C UL/CSA, DESINA MOTION-CONNECT 500 Type of delivery: to 69 m ring from 70 m drum Dmax=13.6 mm, Length (m)= 0 + 10 + 5 + 0	66,51	66,51	66,51	6,901 KG	0x0x0	5	1	1	ST									LF-3/7 Da N	N
290	1	6SL3055-0AA00-5CA2	SINAMICS SENSOR MODULE SMC30 FOR INCREMENTAL ENCODER: TTL/HTL OR KOMBI ENCODER SSI WITH INCREMENTAL TRACES OR KOMBI ENCODER SSI WITHOUT INCREMENTAL SIGNALS / WITHOUT DRIVE-CLIQ CABLE 30 MM WIDTH	99,37	99,37	99,37	0,58 KG	0x0x0	10	1	1	ST									LF-3/7 Da N	EAR99H
300	1	6SL3060-4AW00-0AA0	SINAMICS DRIVE-CLIQ CABLE (P20/P20) LENGTH 1.20 M	13,97	13,97	13,97	0,069 KG	0x0x0	10	1	1	ST									LF-3/7 Da N	N
310	1	6FX5002-2CA12-1BF0	Signal cable pre-assembled type: 6FX5002-2CA12 (HTL and TTL encoder) 4x 2x 0.34+0.5 C without sub-D connector UL/CSA, DESINA MOTION-CONNECT 500 Dmax=9.3 mm Length (m)= 0 + 10 + 5 + 0	51,37	51,37	51,37	1,91 KG	0x0x0	5	1	1	ST									LF-3/7 Da N	N
320	1	1FP1014-1DB42-1AK4-1KG11-0L05	SIMOTICS GP-VSD4000 Motor type: 1RV4164B IEC LV motor, synchronous Reluctance motor, self-ventilated Super Premium Efficiency Temperature class 155(F) according to 135(B) Aluminum enclosure, IP55 Only for converter operation 4-pole/ BCL600+ 15 kW (1500 rpm) 17.3 kW (1800 rpm) 25.0 kW (2610 rpm) 3 AC 50 Hz 380 VY 3 AC 60 Hz 440 VY 3 AC 87 Hz 380 VD IM B 3, 1 P16000 resistance thermometer (2 terminals) Terminal box at top C11-Built-on encoder Sendi 5020 (HTL) L105-Normative cylindrical shaft extension NDE (non drive end) according to EN 50347	936,04	936,04	936,04	105,5 KG	0x0x0	40	1	1	ST									LF-3/7 Da N	N

Součet zakaznických cen v EUR:	0,00	0,00
Součet prodloužené záruky EEO (jednotek EEO/EUR)	0	0,00
Celková cena sestavy EUR:	21 776,98	
Orientační cena v Kč:	561 083,95	