Příloha č. 1 dodatku:

PROHLÁŠENÍ DODAVATELE

Dlouhodobá nedostupnost zesilovače Pioneer SX-20DAB-K



pro veřejnou zakázku

"Dodavatel audiovizuální techniky pro projekty OP VVV na ESF MU 2019"

Dodavatel: ApS Brno s.r.o., Božetěchova 2, 612 66 Brno IČ : 00 54 35 35 , DIČ : CZ 00 54 35 35

Tímto prohlašujeme, že u nabídnutého zesilovače Pioneer SX-20DAB-K černý dochází k dlouhodobému výpadku v distribuci. Z tohoto důvodu navrhujeme adekvátní náhradu splňující veškeré požadované parametry—**ONKYO TX-8220 černý**.

Technický list přikládám.

Děkujeme za akceptaci.

V Brně dne 7.8.2019





razítko a podpis dodavatele



TX-8220 Stereo Receiver

BLACK SILVER













With Hi-fi Power On Tap, the TX-8220 Offers You More

Universal connectivity meets pure analog amplification in a simple hub that sounds a whole lot better than its modest price suggests. All the essentials are covered with digital audio inputs for TV and BD/DVD player connection, along with four analog line-level inputs for CD player and everything else. But the TX-8220 also takes value up a notch with MM phono input for turntable, DAB+ and FM/RDS radio tuners with 40 presets, and built-in Bluetooth® technology. A few taps on a touchscreen, trackpad, or mouse has music from apps flowing out of your loudspeakers thanks to Auto Connect. See how bass, treble, and balance controls, speaker A/B Drive, and subwoofer pre-out let you calibrate tone to suit unique speakers, customize a multi-zone setup, and enhance LFEs in film soundtracks. Boasting clean, minimal design with maximum versatility, the TX-8220 is great value.

HIGHLIGHTS

- 100 W/Ch Hi-Current Amplification System
- Bluetooth® Audio Streaming Technology for Almost Any Device
- · DAB+ and FM/RDS Radio Tuners with
- · MM Phono, Analog, and Digital Audio Inputs
- Hi-Current Discrete Amplification System

ADVANCED FEATURES

- 100 W/Ch Stereo Power (6 Ω, 1 kHz, 10%, 1 Channel Driven, IEC)
- Stream from Mobiles, Smartphones, Tablets, Laptops, and PC via Bluetooth Version 4.1 (A2DP/AVRCP) with Bluetooth Standby and Auto Connect Functions
- DAB+ and FM/RDS Radio Tuners with 40-Station **Memory Presets**
- · Radio Station Preset Naming (Up to 8 Characters)
- WRAT (Wide Range Amplifier Technology) with Massive Hi-Current El Transformer, Custom Power Capacitors, and Low Impedance Drive
- Non-Phase-Shift Amp Circuitry with Discrete
- · Optimum Gain Volume Circuitry
- 192 kHz/24-bit* (PCM1754) Digital-to-Analog Converter
- Direct Mode for Source-Authentic Audio Reproduction
- * 96 kHz/24-bit D/A conversion

CONNECTION FEATURES

- 2 Digital Audio Inputs (I Optical and I Coaxial)
- 4 Analog RCA Inputs and I Line Output
- . Phono Input with MM Equalizer
- Two Pairs of Speaker Posts with Screw Knobs
- 6.35 mm Headphone Jack

ADDITIONAL FEATURES

- Front-panel Bass/Treble/Balance Buttons
- * Front-panel Speaker A/B Drive Selector Button
- · 3-Mode Display Dimmer (Normal/Dim/Dimmer)
- · Sleep Timer and Battery-free Memory Back-up · Full-function RI (Remote Interactive) Remote Controller
- · Bluetooth Standby Mode and Auto Standby



Bluetooth® Transforms Mobile Audio Into Room-filling Sound

With low-latency Bluetooth 4.1 wireless technology, you can stream almost any audio that's playing on your smartphone, tablet, laptop, or PC applications. Auto Connect function makes pairing up and playing back your music much faster and easier than before, with enhanced stability reducing loss in audio quality.



FM/DAB+ Tuner with 40 Memory Presets

Scan and save 40 FM/RDS and DAB+ radio stations for easy one-touch recall anytime. RDS function offers detailed station and song information as you listen.

Bring a huge variety of programming to your listening space, from news and sport to music and talk radio.



Connects Your Turntable, CD Player, TV, and Media Streamer

Aimed at music and film lovers that want to add great sound to a variety of media sources, the TX-8220 comes extensively equipped with audio connections. The receiver is one of the few at this price to include a quality MM phono stage for your turntable. It also has digital inputs to route audio from TV through amp and speakers. Four analog line inputs are included should you prefer your source device to handle D/A conversion, or for connecting a phone or DAP.

Rich and Powerful Sound

Pair the TX-8220 with your choice of loudspeakers and add immersive sound to everyday entertainment, from streaming audio to TV programs, vinyl, and CD. Discrete amplifiers, massive El transformer, and customized capacitors deliver ample driving power with low distortion. High current grips the speaker cones for more accurate control, restoring vitality and detail to music. Wide-range non-phase-shift circuitry, meanwhile, clearly focuses the audio image.

High Current and Low Impedance Architecture

Dynamic passages in music and film soundtracks can see impedance spike and dip dramatically for short periods. This can place up to 10 times the usual load on your amplifier, and if it can't meet power demands, sound quality suffers. Onkyo's high-current low-impedance WRAT design uses a massive El transformer to drive your speakers accurately, even under heavy loads.

A/B Speaker Posts for Multi-room Audio

TX-8220 features two sets of speaker posts enabling connection of two pairs of speakers. The receiver is designed to drive either a single pair of speakers rated at 4–16 Ω , or two pairs of $8-16~\Omega$ speakers, allowing you to enjoy the same audio source in two rooms at once, or to easily switch between two sets of speakers.

Bass, Treble, and Balance Controls

Bass, treble, and balance buttons are useful for adjusting the tone characteristics of your music for satisfying response with any speaker type. Carefully designed tone circuits-which some receivers don't include-let you personalize sound to taste with no perceived loss in audio quality.

SPECIFICATIONS

A		
Amplifier Section		
Power Output	100 W/Ch	
and the contract of the	(6 Ω, 1 kHz, 1%, 1 Channel Driven, IEC)	
Dynamic Power	140 W (3 Ω, Frant)	
	120 W (4 Ω, Frant)	
	80 W (8 Ω, Front)	
THD+N (Total Harmor		
	0.08% (20 Hz-20 kHz, Half Power)	
Input Sensitivity and Imp		
	Line 450 mV/40 kΩ	
	Phono MM 10 mV/50 kΩ (IHF-A)	
Rated RCA Output Lev		
	420 mV/2,2 kΩ (Line-Out)	
	2.8 mV/3.3 kΩ (Subwoofer Pre-Out)	
Phono Overload	40 mV (MM, 1 kHz, 0.5%)	
Frequency Response	10 Hz-100 kHz/+1 dB, -3 dB (Direct Mode)	
Tone Control	±12 dB, 100 Hz (Bass)	
	±12 dB, 10 kHz (Treble)	
Signal-to-Noise Ratio	100 dB (IHF-A, Line In, Speaker Out)	
	93 dB (IHF-A, Phono In, Speaker Out)	
Speaker Impedance	4 Ω=16 Ω (A or B)	
	8 Ω–16 Ω (A + B)	
Headphone Output Imp	pedance	
	390 Ω	
Headphone Rated Outp	ut 60 mW (32 Ω, 1 kHz, 10%)	
Tuner Section		
Tuning Frequency Rang		
FM	87.5 MHz-108 MHz	
FM/DAB+ Preset Memo		
	ry 40 Stations	
General		
Power Supply	AC 220-240 V, 50/60 Hz	
Standby Power Consum	ption	
	0.4 W	
No-Sound Power Cons	umption	
	20 W	
Dimensions (W x H x [D) 435 × 149 × 328 mm	
Walshe	70 km	

Weight CARTON

Dimensions (W >	H x D) 533 x 234 x 401 mm	
Weight	8.8 kg	

7.0 kg

Supplied Accessories



Text on receiver may vary with region