

**Invoice address:**

FYZIKALNI USTAV AVCR v.v.i.

NA SLOVANCE 1999/2  
**CZ 182 21 PRAHA 8**

**Delivery address:**

ELI Beamlines - sklad  
FZU AV CR

Prumyslova 836  
**CZ 252 41 Dolni Brezany**

**Order Acceptance** 9 19103884 - 2019-10-24

**Customer ID:** 100116  
**VAT-ID:** CZ68378271  
**Your Order:** 19912164  
**dated:**  
**Orderer:** Mr. Ing. Andrej Urbanec

**Our reference:** Jiri, Drbohlav  
**Direct dial:** +420 257 923 888  
**E-Mail:** Jiri.Drbohlav@pfeiffer-vacuum.cz  
**Representative:** Martin Misina

Item	Article	Quantity	Delivery date	Price in EUR
1.0	<b>PT R40 351</b> MPT 200, Digital Pirani Cold Cathode Gauge DN 40 CF-F Analog / Relays - Method of measurement: Pirani/Cold Cathode - Measurement range: 5E-9 – 1E3 hPa - Accuracy: 100 – 1000 hPa: ± 50 % - Accuracy: 10 – 100 hPa: ± 30 % - Accuracy: 2 · 10 <sup>-3</sup> – 10 hPa: ± 10 % - Accuracy: 1 · 10 <sup>-8</sup> – 2 · 10 <sup>-3</sup> hPa: ± 25 % - Repeatability: 1 · 10 <sup>-2</sup> – 10 hPa: ± 2 % - Repeatability: 1 · 10 <sup>-8</sup> – 1 · 10 <sup>-2</sup> hPa: ± 7 % Insensitive to gas inrush Customizable to vacuum application - Nominal diameter: DN 40 CF-F - Supply: Voltage: 24 V DC - Interfaces: RS-485, analog 0-10 V High protection level for industrial applications - Protection category: IP54 - Seal: Metal	1 ks	2019-11-04	
1.5	<b>PT R40 141</b> MPT 200, Digital Pirani Cold Cathode Gauge DN 25 ISO-KF Analog / Relays - Method of measurement: Pirani/Cold Cathode - Measurement range: 5E-9 – 1E3 hPa - Accuracy: 100 – 1000 hPa: ± 50 % - Accuracy: 10 – 100 hPa: ± 30 % - Accuracy: 2 · 10 <sup>-3</sup> – 10 hPa: ± 10 % - Accuracy: 1 · 10 <sup>-8</sup> – 2 · 10 <sup>-3</sup> hPa: ± 25 % - Repeatability: 1 · 10 <sup>-2</sup> – 10 hPa: ± 2 % - Repeatability: 1 · 10 <sup>-8</sup> – 1 · 10 <sup>-2</sup> hPa: ± 7 %	1 ks	2019-11-04	

**Order Acceptance**      9 19103884   -   24.10.2019

Item	Article	Quantity	Delivery date	Price in EUR
	Insensitive to gas inrush Customizable to vacuum application - Nominal diameter: DN 25 ISO-KF - Supply: Voltage: 24 V DC - Interfaces: RS-485, analog 0-10 V High protection level for industrial applications - Protection category: IP54 - Seal: Metal			
2.0	<b>PT 348 223 -T</b> Connection cable, RS 485 HiPace-TC/DigiLine Transmitter M12/SUB-D, 9-pole length: 3 m	1 ks	2019-11-04	
3.0	<b>PT 348 250 -T</b> Gauge Cable DigiLine CPT/RPT/PPT/HPT/MPT AR to Single/Dual/Maxi Gauge controller, length 3 m	1 ks	2019-11-04	
4.0	<b>PT G28 040</b> TPG 361, SingleGauge Display and control unit for one gauge 100-250 V AC, 50/60 Hz  For operation of one gauge with analog output signal - Brilliant display - Simple to operate - two configurable relay set points - versatile connectivity - USB - RS-485 -Ethernet - Direct data storage on USB flash memory (data and settings) - can be used as table top or as rack mount unit	1 ks	2019-11-04	
5.0	<b>P 4564 309 YU</b> Mains cable, 230V AC, (DE) 1 mm <sup>2</sup> , length: 2,5 m with Schuko-plug CEE (7) VII Euro style EN 60320/C13  Charges for transport and packing will be issued in our invoice.	1 ks	2019-11-04	

**Versicherung** **5,00**

Value of goods	2.501,61
Taxable amount	2.506,61
VAT 0,0%	0,00
<b>Total amount</b>	<b>2.506,61</b>

**Pfeiffer Vacuum Austria GmbH**

**Order Acceptance** 9 19103884 - 24.10.2019

<b>Item</b>	<b>Article</b>	<b>Quantity</b>	<b>Delivery date</b>	<b>Price in EUR</b>
-------------	----------------	-----------------	----------------------	---------------------

---

**Terms of delivery:** FCA

**Delivery method:** UPS - United Parcel Service

**Payment:** 30 dní po vystavení, netto

**Net weight in kg:** 3,200

- Anzeige / Advert -

**VACUUM SOLUTIONS FROM A SINGLE SOURCE**  
**[www.pfeiffer-vacuum.com](http://www.pfeiffer-vacuum.com)**