

Příloha č. 1 smlouvy č. 3155/2016 - Technická specifikace zařízení pro výslech utajovaného svědka

Video Specifications Transmission Speed

H.323 64 Kbps – 2 Mbps

Video Standards

H.261, H.263, H.263+/++

Live Video Resolution

4CIF (704 x 576 pixels) Rx
CIF (352 x 288 pixels)
SIF (352 x 240 pixels)
QCIF (176 x 144 pixels)

Video Frame Rate

Up to 15 fps: 64 – 320 Kbps
Up to 30 fps: 384 Kbps +

Video Inputs

Composite, S-video

Video Outputs

S-video, Composite, VGA

PTZ Cameras Supported

Sony D100
Sony EVI-D30/31
Support for Canon camera available

Far-End Camera Control (FECC)

Complies with H.281 Annex Q

Data Specifications Data Ports

RS-232 control port (for Serial API or PTZ camera control)

Data sharing

Complies with H.239 ITU-T standard
Utilizes HD Data utility for sharing
PC desktop applications and presentations

Data Video Resolution

SVGA (800 x 600)
VGA (640 x 480)
Up to 4CIF for PAL/NTSC monitors

Security Specifications

Encryption Complies with H.235 (AES) ITU-T standard

Audio Specifications Audio Standards

G.711, G.722, G.723.1, G.728, G.729

Audio Inputs

Microphone omni and uni Line level RCA, L/R

Audio Outputs

Line level RCA, L/R

Audio Features

Full duplex echo cancellation
Automatic noise suppression
Ability to turn off internal echo canceller DTMF tone generation

Networking Specifications

Standards Supported ITU-T H.323 v4

Networking

Integrated 10/100 Ethernet NIC
DHCP
WINS
DNS
FTP
HTTP with DAA
Telnet

Software Upgrades

	Via HD Upgrade utility or the SpeedPoint device via FTP Upgrade availability notification
Phone Book Capacity	1000+ entries Multit-language support Unicode support
H.323 QoS Features	DiffServ IP Precedence Firewall port sync NAT IP address mask Port pinholing Adaptive Bandwidth Adjustment Packet ordering Packet duplication control Jitter correction Lip sync correction Overhead prediction
Streaming Specifications	HD Simulcast™ Multicast Streaming Video Multicast to Emblaze-VCON's Broadcast Viewer, Quicktime Viewer and other Multicast viewers with integrated SDP listeners
Unicast Streaming Video	Unicast to Quicktime viewers Data rate downspeeding Multicast-unicast in same call: Up to 15 unicast streams at 384 Kbps during multicast session Up to 10 unicast streams at 384 Kbps during 384 Kbps call + multicast
Interactive Multicast	Participate in any Emblaze-VCON Interactive Multicast session Uses bandwidth-efficient IP multicast
Other Specifications	Browser-based Management Uses DAA (Digest Access Authentication) Dial/Hangup calls Phone book management Device and network configuration Streaming start/stop/view Camera and volume control Call status Diagnostics Call detail reports
Control	Hand-held remote control Internal infrared receiver
Physical Dimensions	Dimensions: 260(W) x 210(D) x 40(H)mm Weight: 2.1Kg