

**Invoice address:**

FYZIKALNI USTAV AVCR v.v.i.

NA SLOVANCE 1999/2  
**CZ 182 21 PRAHA 8**

**Delivery address:**

ELI Beamlines - sklad  
FZU AV CR

Prumyslova 836  
**CZ 252 41 Dolni Brezany**

**Order Acceptance** 9 20102916 - 2020-10-01

**Customer ID:** 100116  
**VAT-ID:** CZ68378271  
**Your Order:** 0020950099  
**dated:**  
**Orderer:** Mr. Ing. Andrej Urbanec

**Our reference:** Apolena Vondraskova  
**Direct dial:** +420 257 923 888  
**E-Mail:** apolena.vondraskova@pfeiffer-vacuum.cz  
**Representative:** Martin Misina

Item	Article	Quantity	Delivery date	Price in EUR
1.0	<p><b>PT M16 212 211</b>  QMG 250 M2, PrismaPro Compact mass spectrometer mass range: 1-200 amu with input/output-module IO250</p> <p>Compact mass spectrometer</p> <ul style="list-style-type: none"> <li>- Mass range: 1-200 amu</li> <li>- Operating pressure max.: Faraday: <math>5 \times 10^{-4}</math> hPa</li> <li>- Operating pressure max.: EM: <math>5 \times 10^{-5}</math> hPa</li> </ul> <p>for residual gas analysis at high and ultra-high vacuum and for gas analysis</p> <ul style="list-style-type: none"> <li>- Flange (in): DN 40 CF-F</li> <li>- Supply: Voltage: 100 – 240 V AC</li> <li>- Interfaces: Ethernet</li> <li>- Detector: EM/Faraday</li> <li>- Ion source: Open, 2 filaments</li> <li>- Filament: Iridium, Y<sub>2</sub>O<sub>3</sub>-coated</li> <li>- Bakeout temperature: analyzer: 300 °C</li> <li>- Connection: 0°</li> </ul> <p>PV MassSpec-Software, for Windows 10, 8.1 &amp; 7 for measurement, storage and display of measurement data</p> <ul style="list-style-type: none"> <li>- Leak detection and vacuum diagnosis with just one click</li> <li>- Simple definition of measurement recipes</li> <li>- Automated measurement routines via included sequencer</li> <li>- Automatic calibration and tuning</li> <li>- Mass spectrometer data can be linked with external signals with I/O-Option:</li> <li>- Output: Analog: 8 x, 0-10 V / 16 Bit</li> <li>- Output: Digital: 10 x, 24 V</li> <li>- Input: Analog: 8 x, <math>\pm 10</math> V / 16 Bit</li> <li>- Input: Digital: 5 x, 24 V</li> <li>- Connection for gauge: Connector for ActiveLine- or DigiLine-</li> </ul>	1 ks	2020-11-10	

**Order Acceptance** 920102916 - 01.10.2020

Item	Article	Quantity	Delivery date	Price in EUR
	Transmitter with analog-relays-option			
2.0	<b>P 4564 309 YU</b> Mains cable, 230V AC, (DE) 1 mm <sup>2</sup> , length: 2,5 m with Schuko-plug CEE (7) VII Euro style EN 60320/C13	1 ks	2020-11-10	
	<b>Versicherung</b>			<b>22,00</b>
	<b>Fracht</b>			<b>20,00</b>
	<b>Verpackung</b>			<b>58,00</b>

Value of goods	11.472,00
Taxable amount	11.572,00
VAT 0,0%	0,00
<b>Total amount</b>	<b>11.572,00</b>

**Pfeiffer Vacuum Austria GmbH**

Z důvodu změn nákupních cen materiálů a nárůstu nákladů na pracovní sílu, jsme nuceni k mírné úpravě cen výrobků v některých produktových skupinách. Nové ceny budou platit od 1. listopad 2020.

**Terms of delivery:** FCA

**Delivery method:** UPS - United Parcel Service

**Payment:** 30 dní po vystavení, netto

**Net weight in kg:** 6,740

- Anzeige / Advert -

**VACUUM SOLUTIONS FROM A SINGLE SOURCE**  
**www.pfeiffer-vacuum.com**