

Nabídka: Monitoring vibrací

Kalkulace

| Pozice | Množ. | Objednací číslo a popis | Jednotková cena bez DPH | Cena celkem bez DPH |
|---------------|----------------|---|------------------------------------|--------------------------------|
| 1.1.1 | 1 ks | X20CM4810 X20 analog input module, for vibration measurement and analysis of condition monitoring exercises, 4 IEPE analog inputs, 51,5625 kHz sampling frequency, 24-bit converter resolution | 12 757,60 Kč | 12 757,60 Kč |
| 1.1.2 | 1 ks | X20BM31 X20 bus module, for double-width modules, 24 VDC keyed, internal I/O supply continuous | 308,80 Kč | 308,80 Kč |
| 1.1.3 | 1 ks | X20TB12 X20 terminal block, 12-pin, 24 VDC keyed | 88,80 Kč | 88,80 Kč |
| 1.1.4 | 1 ks | 0ACS100A.00-1 Acceleration sensor, nominal sensitivity 100 mV/g, top exit | 3 035,20 Kč | 3 035,20 Kč |
| 1.1.5 | 1 ks | 0ACS100A.90-1 Acceleration sensor, nominal sensitivity 100 mV/g, side exit | 4 136,00 Kč | 4 136,00 Kč |
| 1.1.6 | 1 ks | 0ACC0050.01-1 Cable for acceleration sensor, length 5 m, 2x 0.34 mm ² , M12 socket on sensor side, can be used in cable drag chains, UL listed | 577,00 Kč | 577,00 Kč |
| 1.1.7 | 1 ks | 0ACC0100.01-1 Cable for acceleration sensor, length 10 m, 2x 0.34 mm ² , M12 socket on sensor side, can be used in cable drag chains, UL listed | 880,00 Kč | 880,00 Kč |
| Pozice | Množ. | Objednací číslo a popis | Jednotková cena bez DPH | Cena celkem bez DPH |
| Množ. | Koncept | | Jednotková cena bez DPH | Cena celkem bez DPH |
| 1 | B&R-Product | | 21 783,40 Kč | 21 783,40 Kč |

Nabídka: Řídící systém

Kalkulace

| Pozice | Množ. | Objednací číslo a popis | Jednotková cena bez DPH | Cena celkem bez DPH |
|--------|-------|---|----------------------------|------------------------|
| 1.1.1 | 1 ks | X20CP0484 X20 Compact-S CPU, ARM Cortex A9-667, 256 MByte DDR3 RAM, 64 kByte FRAM, 2 GByte Flash Drive on board, 2 USB ports, 1 RS232 interface, 1 POWERLINK interface, 1 Ethernet port 10/100 Base-T, capability for X20 interface slots. Order bus base, power supply module and terminal block separately! | 14 408,00 Kč | 14 408,00 Kč |
| 1.1.2 | 1 ks | X20PS9600 X20 power supply module, for Compact-S CPU and internal I/O supply, X2X Link supply | 792,80 Kč | 792,80 Kč |
| 1.1.3 | 1 ks | X20BB52 X20 Compact-S bus base, for Compact-S CPU and Compact-S CPU power supply module, base for integrated RS232 interface, X20 connection, X20 locking plates X20AC0SL1/X20AC0SR1 (left and right) included | 769,60 Kč | 769,60 Kč |
| 1.1.4 | 1 ks | X20PD2113 X20 potential distributor module, 6x GND, 6x 24 VDC, with supply option, integrated microfuse | 638,40 Kč | 638,40 Kč |
| 1.1.5 | 1 ks | X20PD0053 X20 potential distributor module, 6x 5 VDC, 6x GND | 1 671,20 Kč | 1 671,20 Kč |

| Pozice | Množ. | Objednáací číslo a popis | Jednotková cena bez DPH | Cena celkem bez DPH |
|---------------|----------------|--|------------------------------------|--------------------------------|
| 1.1.6 | 2 ks | X20AT4222 X20 temperature input module, 4 inputs for resistance measurement, PT100, PT1000, resolution 0.1°C, 3-wire connections | 4 356,00 Kč | 8 712,00 Kč |
| 1.1.7 | 1 ks | X20AI4632 X20 analog input module, 4 inputs, ±10 V or 0 to 20 mA, 16-bit converter resolution, configurable input filter, oscilloscope functions | 4 728,80 Kč | 4 728,80 Kč |
| 1.1.8 | 1 ks | X20DM9324 X20 digital mixed module, 8 inputs, 24 VDC, sink, configurable input filter, 4 outputs, 24 VDC, 0.5 A, source, 1-wire connections | 1 408,00 Kč | 1 408,00 Kč |
| 1.1.9 | 1 ks | X20AP3131 X20 energy measurement module, 3 analog inputs, 480 VAC, 50/60 Hz, 4 analog inputs, 5 A AC, calculation of effective, apparent, reactive power and reactive energy, calculation of RMS values, 240 V keyed, Net time function | 3 739,20 Kč | 3 739,20 Kč |
| 1.1.10 | 1 ks | X20ZF0000 X20 dummy module (non-functional) | 88,80 Kč | 88,80 Kč |
| 1.1.11 | 1 ks | X20CMR100 X20 cabinet monitoring module, integrated temperature and humidity sensor, operating data recorder, integrated Technology Guard | 1 716,80 Kč | 1 716,80 Kč |
| 1.1.12 | 1 ks | X20DC1176 X20 digital counter module, 1 ABR incremental encoder, 5 V, 600 kHz input frequency, 4x evaluation, encoder monitoring, Net time function | 3 409,60 Kč | 3 409,60 Kč |
| 1.1.13 | 9 ks | X20BM11 X20 bus module, 24 VDC keyed, internal I/O supply continuous | 154,40 Kč | 1 389,60 Kč |
| Pozice | Množ. | Objednáací číslo a popis | Jednotková cena bez DPH | Cena celkem bez DPH |
| 1.1.14 | 10 ks | X20TB12 X20 terminal block, 12-pin, 24 VDC keyed | 88,80 Kč | 888,00 Kč |
| 1.1.15 | 1 ks | X20BM32 X20 bus module, for double-width modules, 240 VAC keyed, internal I/O supply continuous | 572,80 Kč | 572,80 Kč |
| 1.1.16 | 1 ks | X20TB32 X20 terminal block, 12-pin, 240 VAC keyed | 132,00 Kč | 132,00 Kč |
| Množ. | Koncept | | Jednotková cena bez DPH | Cena celkem bez DPH |
| 1 | X20 system | | 45 065,60 Kč | 45 065,60 Kč |