

Austria & C.E. Europe Pfeiffer Vacuum Austria GmbH Diefenbachgasse 35 AT 1150 Wien

Phone +43 1 894 17 04 Fax +43 1 894 17 07 www.pfeiffer-vacuum.com office@pfeiffer-vacuum.cz

Invoice address:

USTAV FYZIKALNI CHEMIE J. HEYROVSKEHO AVCR, v.v.i.

DOLEJSKOVA 3 CZ 182 23 PRAHA 8

Delivery address:

USTAV FYZIKALNI CHEMIE J. HEYROVSKEHO AVCR, v.v.i. NAKUPNI ODDELENI

DOLEJSKOVA 3 CZ 182 23 PRAHA

Order Acceptance

Representative:

9 2 2 1 0 2 9 6 1 - 2 0 2 2 - 0 9 - 3 0

Our reference:

Direct dial: +420 257 923 888

002230001 **E-Mail**:

@pfeiffer-vacuum.cz

dated:

VAT-ID:

Customer ID:

Your Order:

Orderer:

Item Article Quantity Delivery date Price in EUR

2 ks

1 ks

1.0 **PM 193 310 BT**

Sales Promotion Turbo HiPace 700 Package DN 160 CF-F with OmniControl und AC

102151

CZ61388955

HiPace 700; DN 160 CF-F;

with TC 400; OmniControl 400;

power cable; interface cable, connection cable;

and air cooling

High-performance turbomolecular pump

- Pumping speed for N2: 685 I/s
- Ideal for all standard processes
- Mounting orientation: in any orientation
- Protection category: IP54
- Flange (in): DN 160 CF-F
- Flange (out): DN 16 ISO-KF/G 1/4"
- Venting connection: G 1/8"
- Operating voltage: 24 (± 5 %) V DC
- Interfaces: RS-485, Remote
- Electronic drive unit: with TC 400
- Cooling method, standard: Water
- Cooling method, optional: Air

comprehensive accessories extend the range of applications

2.0 **PM 193 301 BT**

Sales Promotion Turbo HiPace 80 Package DN 63 CF-F with OmniControl und AC

HiPace 80; DN 63 CF-F;

with TC 110; OmniControl 200;



Order Acceptance

922102961 _ 30.09.2022

ltem Article Quantity **Delivery date** Price in EUR

3 ks

power cable; interface cable, connection cable; and air cooling

High-performance turbomolecular pump

- Pumping speed for N2: 67 l/s

Ideal for all standard processes, bakeable (optional)

- Mounting orientation: in any orientation
- Protection category: IP54
- Flange (in): DN 63 CF-F
- Flange (out): DN 16 ISO-KF/G 1/4"
- Venting connection: G 1/8"
- Operating voltage: 24 (± 5 %) V DC
- Interfaces: RS-485, Remote
- Electronic drive unit: with TC 110
- Cooling method, standard: convection
- Cooling method, optional: Air/Water

comprehensive accessories extend the range of applications

3.0 P 4564 309 ZA

Mains cable, 230V AC, (DE) length: 3m with Schuko-plug CEE (7) VII Euro style EN 60320/C13

Charges for transport and packing will be issued in our invoice.

Should the costs underlying Pfeiffer Vacuum's calculation, in particular for personnel, material, raw materials, transport or energy - also due to exchange rate fluctuations - change by at least 5 % after conclusion of the contract, Pfeiffer Vacuum is entitled to adjust the price accordingly. The price adjustment shall be made in accordance with Pfeiffer Vacuum's calculation while maintaining the calculated profit. Pfeiffer Vacuum shall notify the customer of the price adjustment without undue delay and provide comprehensible reasons therefor. Insofar as the change in the underlying costs is due to a circumstance for which Pfeiffer Vacuum is responsible and which is contrary to the diligence of a prudent business practices, no price increase may be affected. In the event that a price increase exceeds 10 %, the customer shall have the option to cancel the relevant order free of charge for a period of two weeks from receipt of Pfeiffer Vacuum's notification. Such cancellation must be made in writing.

Fracht 430,00

> Value of goods 24.090,00 Taxable amount 24.520,00 VAT 0,0% 0,00

24.520,00 Total amount

Pfeiffer Vacuum Austria GmbH

2 / 3



Order Acceptance

922102961 _ 30.09.2022

Item Article Quantity Delivery date Price in EUR

Terms of delivery: FCA

Delivery method: UPS - United Parcel Service

Payment: 30 dní po vystavení, netto Net weight in kg: 51,100

Anzeige / Advert-

VACUUM SOLUTIONS FROM A SINGLE SOURCE www.pfeiffer-vacuum.com