

## Swing-out rotor 11150

## Rectangular bucket 13220 (1 set = 2 pcs)

- Max. plate height: 51 mm
- Max. speed (6-16S / 6-16KS): 4,100 rpm
- Max. RCF (6-16S / 6-16KS): 3,007 x g
- Max. load per carrier: 300 g
- Tmin at maximum speed: <4°C
- Angle: 90°



## Swing-out rotor 11150

## Rectangular bucket 13221 (1 set = 2 pcs) with plate holder 17979

- Max. plate height: 56 mm
- Max. speed (6-16S / 6-16KS): 4,500 / 5,100 rpm
- Max. RCF (6-16S / 6-16KS): 3,622 / 4,653 x g
- Max. load per carrier: 450 g
- Tmin at maximum speed: <4°C
- Angle: 90°



## Plate



Description	MTP (without lid)	MTP (with lid)	DWP	PCR plate 96-fold
W x D x H [mm]	128 x 86 x 15	128 x 86 x 17.5	128 x 86 x 44.5	128 x 86 x 20

## Adapter

for rectangular bucket 13220



Bore diameter x length [mm]	-			
Plates per rotor	12	8	4	8
Centrifuging radius [mm]	160			
Item no.	-			


## Plate



Description	MTP (without lid)	MTP (with lid)	DWP	PCR plate 96-fold
W x D x H [mm]	128 x 86 x 15	128 x 86 x 17.5	128 x 86 x 44.5	128 x 86 x 20

## Adapter

for rectangular bucket 13221



Bore diameter x length [mm]	-			
Plates per rotor	12	12	4	8
Centrifuging radius [mm]	160			
Item no.	17979			