

Adresa:

FYZIKALNI USTAV AVCR v.v.i.
[REDACTED]

NA SLOVANCE 1999/2
CZ 182 21 PRAHA 8

Pobočka Praha
Novodvorská 1062/12
CZ 142 01 Praha 4
+420 257 923 888
+420 257 923 014
office@pfeiffer-vacuum.cz

Nabídka 9 22002435 - 2023-01-13

Zákaznické číslo: 100116
DIČ: CZ68378271

Datum popptávky: 2022-11-15

Zpracovává:	[REDACTED]
Přímá linka:	[REDACTED]
E-Mail:	[REDACTED]
Náš kontakt:	[REDACTED]
Platná do:	2023-02-13
Dodací lhůta:	12-14 týdnů

Vážení

děkujeme Vám za Váš zájem o vakuové komponenty a technologie firmy PFEIFFER Vacuum a zasíláme Vám naši nabídku:
Pro nabídku a dodávku platí Všeobecné obchodní podmínky firmy Pfeiffer Vacuum.

Pol.	Produkt	Množství	Sleva	Cena v EUR	
				za MJ	Celkem

[REDACTED]					
------------	--	--	--	--	--

Nabídka 9 22002435 - 13.01.2023

Pol.	Produkt	Množství	Cena v EUR		
			za MJ	Celkem	
2.0	PD 100 180 -T Package HiScroll 6 BC800, 100-240V, 50/60Hz, 1-ph MS R&D (RDC) HiScroll Package including: HiScroll 6, exhaust silencer ES 25 M incl. clamps Dry and oil-free scroll vacuum pump Inkl. ATEX II 3/-G Ex h IIC T4 Gc X +5 °C ≤ Ta ≤ +40 °C Pumping speed: 6.1 m ³ / h Ultimate pressure without gas ballast: 1,5 x 10e-2 hPa Ultimate pressure with gas ballast stage 1: 7 x 10e-2 hPa Ultimate pressure with gas ballast stage 2: 4 x 10e-1 hPa Super silent: Best for use in quiet environments such as in the laboratory Noise level: <48dB (A) Low vibrations and compact design Low operating costs thanks to the highest quality, short maintenance times and long maintenance intervals Connection flange (inlet): DN 25 ISO-KF Connection flange (outlet): DN 25 ISO-KF Mains connection: 50 / 60Hz: 100 — 127 / 200 — 240 V AC (±10 %) Industry 4.0 capable: Operation with other intelligent products such as turbopumps via RS-485 Safe operation with built-in check valve Performance as required: stable pumping speed and short cycle times Sustainable: 15% higher efficiency of the drive system, less heat generation and less cooling demand BC800 drive electronics Active intelligent air cooling Level 1 gas ballast: 11,000 sccm Level 2 gas ballast: 16,000 sccm Leakage rate: <5 x 10e-7 Pa m ³ / s	1 ks			
3.0	P 4564 309 ZA Mains cable, 230V AC, (DE) length: 3m with Schuko-plug CEE (7) VII Euro style EN 60320/C13	2 ks			
4.0	PM 016 333 Protection screen for DN 63 CF-F	1 ks			
5.0	P 4723 010 Y-Connector M12 for RS 485	1 ks			
6.0	PM 061 285 -T Interface cable M12m/M12m length: 10 m	1 ks			
7.0	PE 100 150 -X Adapter RS4 85 M12 SUB-D-15	1 ks			
8.0	PT T03 350 010 PKR 361, Active Pirani/ Cold cathode gauge DN 40 CF-F, high current Compact combination sensor – insensitive to gas inrush - cold cathode gauge according to the inverted magnetron principle - Display range: 1 · 10 ⁻⁹ – 1000 hPa - Measurement range: 1 · 10 ⁻⁸ – 1000 hPa - Accuracy: ± 30 % of reading (10 ⁻⁸ – 100 hPa) - Accuracy: ± 50 % of reading (100 – 1000 hPa) - Supply voltage: 14.5 – 30 V DC - Analog output signal: 0 – 10.5 V, logarithmic - minimum magnetic stray field - optimized for high vacuum applications	1 ks			
9.0	PT 448 250 -T Sensor cable CG for Single/Dual/MaxiGauge length: 3 m	1 ks			

Nabídka 9 22002435 - 13.01.2023

Pol.	Produkt	Množství	Sleva	Cena v EUR	
				za MJ	Celkem

Should the costs underlying Pfeiffer Vacuum's calculation, in particular for personnel, material, raw materials, transport or energy - also due to exchange rate fluctuations - change by at least 5 % after conclusion of the contract, Pfeiffer Vacuum is entitled to adjust the price accordingly. The price adjustment shall be made in accordance with Pfeiffer Vacuum's calculation while maintaining the calculated profit. Pfeiffer Vacuum shall notify the customer of the price adjustment without undue delay and provide comprehensible reasons therefor. Insofar as the change in the underlying costs is due to a circumstance for which Pfeiffer Vacuum is responsible and which is contrary to the diligence of a prudent business practices, no price increase may be affected. In the event that a price increase exceeds 10 %, the customer shall have the option to cancel the relevant order free of charge for a period of two weeks from receipt of Pfeiffer Vacuum's notification. Such cancellation must be made in writing.

Ceny se rozumí "ex works", bez obalu a dopravného, bez DPH.
Obal, dopravné a pojistné jsou účtovány dle skutečných nákladů. Odhad ceny obalu, dopravného a pojistného činí **150,00 EUR**.
Pro nabídku a dodávku platí všeobecné dodací podmínky firmy PFEIFFER Vacuum GmbH dostupné na www.pfeiffer-vacuum.net.

Upozorňujeme, že tato nabídka obsahuje informace spadající do obchodního tajemství firmy Pfeiffer Vacuum Austria GmbH a nesmí být zveřejněna, a to ani v Registru smluv coby součást objednávky. Pro účely zveřejnění dle zákona č.340/2015 Sb. rádi poskytneme redigovanou nabídku neobsahující citlivé informace.

Doufáme, že nabídka odpovídá Vaším požadavkům a jsme připraveni poskytnout další doplňující informace.



Nabídka 9 22002435 - 13.01.2023

Pol.	Produkt	Množství	Sleva	Cena v EUR	
				za MJ	Celkem

Za zboží	8.070,42
Daňový základ	8.070,42
DPH 0,0%	0,00
Celkem k platbě	8.070,42

Pfeiffer Vacuum Austria GmbH

VACUUM SOLUTIONS FROM A SINGLE SOURCE
www.pfeiffer-vacuum.com