




## MAINSTREAM COMPUTING FOR A VARIETY OF BUSINESS USES



ThinkCentre Tiny-In-One devices enable businesses to upgrade displays and computers separately, but still enjoy the space-saving benefits of an all-in-one device.

# ThinkCentre Tiny-In-One 24 Gen 4

Smarter  
technology  
for all

Lenovo

Can be paired with any ThinkCentre Tiny desktop (including models with 65W CPU) to build a 23.8" modular all-in-one in less than a minute – no tools required. Integrated 1080p rotatable camera and mic support web conferencing, and there's also an optional IR camera or optional touchscreen.



## REASONS TO BUY

The new stand is 18% more space-efficient than the previous generation and offers tilt, pivot and increased height adjustment of up to 150mm. Plus there's dedicated space to store a smartphone, and charge it via USB-A or USB-C ports on the side of a connected Tiny.

Like any all-in-one, the display on/off button also powers on the PC. The screen can be pivoted 90 degrees into 'portrait' mode or removed from the stand and connected to an extendable arm for even greater ergonomic flexibility.

Energy Star and EPEAT Silver energy efficiency certifications. TCO Certified – meets independent standards for social and environmental sustainability.

# ThinkCentre Tiny-In-One 24 Gen 4

## DISPLAY

Display Size	23.8"
Touchscreen	optional touchscreen
Resolution	1920x1080
DPI	92.6 dpi
Aspect Ratio	16:9
Contrast Ratio	1000:1
Brightness	250 nits
Pixel Pitch	0.2745 x 0.2745 mm
Color Gamut	72%

## KEY SPECIFICATIONS

Color	Black
Camera	Rotatable 1080p camera
Audio	2x 2W speakers
Stand	Tilt, lift, swivel & pivot stand
Dimensions	Width: 539.8mm (21.25") Depth: 230.4mm (9.07") Height: 446.9 - 596.9mm (17.59 - 23.5")
Weight	6.66kg (14.7lb)

## GREEN CERTIFICATIONS

EPEAT Silver. Energy Star 8.0. UL GREENGUARD. TCO 8.0. TCO Edge 2.0.

## OTHER CERTIFICATIONS

TUV Eye comfort

## CONNECTIVITY

Side/Front I/O	1x USB 3.1 Gen 1 / USB 2.0 (the USB port is only available when a Tiny is installed or a PC is connected via USB upstream port)
Rear I/O	1x DisplayPort (in) port, 1x USB upstream port

## SECURITY & PRIVACY

IR Camera with Windows Hello  
Kensington lock slot

## OPTIONAL MECHANICAL PERIPHERALS

VESA wall mount

## PC COMPATIBILITY

ThinkCentre Tiny Series  
ThinkStation Tiny Series  
ThinkCentre Nano Series

## Recommended for this device



### Lenovo Adjustable Height Arm

Reduce neck & back pain by positioning a VESA-compatible monitor, ThinkCentre M AIO or Lenovo V Series AIO, to the most comfortable height and angle

Extends display out to a range of 64cm (25"), with height adjustment up to 33cm (13")

Can be fitted to desk via a clamp without drilling holes



### Lenovo Kensington MicroSaver Cable Lock

Cut-resistant cable lock to protect against device theft; 5ft/1.5m cable anchors to desk, table or any fixed structure

Tamper-resistant, disk-style lock provides near-impenetrable theft protection, but still allows users to pivot and rotate devices

Fits a wide range of devices and docking solutions based on the Kensington slot design. Dual head locks available to secure 2 devices to one cable



### Premier Support

Talk directly with advanced technical support agents

Support for software & hardware

Next business day onsite repairs

Information presented here may represent the maximum possible configurations for this product, but it does not necessarily reflect what is available in your region. Please ask your rep or check the specifications for specific Part Numbers in your region. © 2020 Lenovo. Products are available while supplies last. Lenovo is not responsible for photographic or typographic errors. Lenovo, the Lenovo logo, ThinkPad, ThinkCentre, ThinkBook, ThinkStation and ThinkVision are trademarks or registered trademarks of Lenovo. 3rd party product and service names may be trademarks of others. Depending on factors such as the processing capability of peripheral devices, file attributes, system configuration and operating environments, the actual data transfer rate of USB connectors will vary and is typically slower than published standards.