

SPECIFIKACE:

OPTICAL

- Light Source: 89 LEDs (18 red, 18 green, 16 blue, 16 amber, 21 lime) 3 W, (1.13 A), 3698 K, 50,000 hours life expectancy
- Color Temperature (range): 2800 to 6500 K
- CRI (3200 K): 90
- Beam Angle: 17° to 54°
- Field Angle: 30° to 85°
- Zoom Range: 17° to 85°
- Lumens (30°): 4,294
- Lumens (73°): 6,661
- Illuminance (30°): 1,980 lux @ 5 m
- Illuminance (85°): 433 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 25,000 Hz

DYNAMIC EFFECTS

- Dimmer: Electronic
- Shutter/Strobe: Electronic
- Zoom: Motorized
- Strobe Rate: 0 to 27 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Built-in Automated Programs: Yes

CONSTRUCTION / PHYSICAL

- Exterior Color: Black

CONNECTIONS

- Power Connection: Edison (Local) plug to Neutrik powerCON
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Data Connectors: 3- and 5-pin XLR

CONTROL

- Control Protocol: DMX, RDM

ELECTRICAL

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

CERTIFICATIONS / QUALIFICATIONS

- CE, MET, FCC
- IP Rating: IP20, dry location