

Název veřejné zakázky: UK2LF – Pomůcky pro zajištění výuky ve studijním programu Radiologická asistence

Část 4: Monitory

Režim a druh veřejné zakázky: veřejná zakázka malého rozsahu na dodávky, dělená na 4 části

Druh výběrového řízení: otevřená výzva na profilu zadavatele

Technická specifikace, minimální technické požadavky zadavatele:

MONITOR KANCELÁŘSKÝ (27“)	iiyama ProLite/XUB2792QSN-B5/27"/IPS/QHD/75Hz/4ms/Black
Úhlopříčka min. 27“	ANO
Výšková nastavitelnost (pivot)	ANO
antireflexní povrch displeje	ANO
Display Port	ANO
LCD monitor Full HD 1920 × 1080, IPS, 16:9, 4 ms, 75Hz, FreeSync, 300 cd/m2, kontrast 1000:1, HDMI 1.4, sluchátkový výstup, VESA	ANO 2560 x 1440, 16:9, 75 Hz, 4 ms 350 cd/m2, 1000:1,
Min. délka záruční doby – 2 roky	ANO, 3 roky
MONITOR DIAGNOSTICKÝ	JVC CL-S300
Protective Filter	ANO
Technology 21.3” color TFT IPS technology	ANO
Display Area 324.86 mm × 433.15 mm	ANO
Pixel Pitch 0.2115 mm × 0.2115 mm	ANO
Contrast Ratio 1500 : 1 (typ.)	ANO

Maximum Luminance 1000 cd/m ² (typ.) 410 cd/m ² / 500 cd/m ² (calibrated)	ANO
Viewing Angle 178° vertical and horizontal	ANO
Visual performance: Native Resolution 1536 × 2048 Display Colors 16.77 million colors from a palette of 280 trillion colors 1.07 billion colors with DisplayPort and 10-bit viewer	ANO
Interface: Input Signals DisplayPort (DisplayPort 1.2a compliant) Output Signal DisplayPort (DisplayPort 1.2a compliant) Plug and Play DDC2B compliant	ANO
Features: Calibration Control Luminance, Gamma, Color temperature Capable of storing 3 sets of LUT (Optional Calibration Kit is required) OSD Information Display Model name, Serial No., Total operating time, Calibration settings (Operating time since last calibration, Luminance, Gamma), Current luminance, Color temperature and Ambient light, DICOM conformance USB Hub USB Rev.2.0 compliant, Self-powered USB upstream connector (x1), USB downstream connector (x2) Other Features Uniformity Equalizer, Hardware pivot, LED indicator, Advanced power management, Human Presence Sensor, Dynamic Gamma, Auto Text Mode, Luminance stabilization, Multiple LUT, Self DICOM check, Self-calibration Approvals ANSI/AAMI ES60601-1 (2005) + A1 (2012), CAN/CSA-C22.2 No. 60601-1 (2014), CE (EN60601-1, EN60601-1-2), RCM, FCC Part15 subpart B Class B , ICES-003-B, VCCI-B, FDA510(k), J-Moss, RoHS	ANO
Dimensions(W x H x D) Landscape : 493 mm × 451.3 / 546.3 mm × 196.5 mm Portrait : 361.5 mm × 517 / 612 mm × 196.5 mm	ANO
Tilt Stand Tilt, Swivel, Portrait / Landscape	ANO
Min. délka záruční doby – 2 roky	ANO – 5 let