

Adresa:

UNIVERZITA PARDUBICE
[REDACTED]

STUDENTSKA 95
CZ 532 10 PARDUBICE

Pobočka Praha
Novodvorská 1062/12
CZ 142 01 Praha 4
[REDACTED]
[REDACTED]

Nabídka 1 23001884 - 2023-09-21

Zákaznické číslo: 102178
DIČ: CZ00216275

Datum poptávky: 2023-09-12

Zpracovává: [REDACTED]
Přímá linka: [REDACTED]
E-Mail: [REDACTED]
Náš kontakt: [REDACTED]
Platná do: 2023-10-12

Vážení

děkujeme Vám za Váš zájem o vakuové komponenty a technologie firmy PFEIFFER Vacuum a zasiláme Vám naši nabídku:
Pro nabídku a dodávku platí Všeobecné obchodní podmínky firmy Pfeiffer Vacuum.

Cena v EUR

Pol.	Produkt	Množství	Cena v EUR
1.0	PK 195 270 -T DUO 1,6, Rotary vane pump 220-240 V, 50/60 Hz with ONFR 16 S, lubrication P3 Consisting of: -Duo 1.6, 1-phase motor, 230-240 V ($\pm 10\%$), 50/60 Hz Dual-stage, high-performance rotary vane pump with a pumping speed of 1.25 m ³ /h at 50 Hz / 1.5 m ³ /h at 60 Hz With single-phase motor, IEC-C14-connector in terminal box With bi-metal-switch for optimum motor protection Integrated gas ballast and safety valve Pump and motor certified according to UL and IEC 61010 For all low and medium vacuum applications First filling of operating fluid included in delivery -OME16 S oil mist eliminator -Clamping ring DN 10-16 ISO-KF -Seal DN 16 ISO-KF -Oil return unit from OME 16 S to Duo 1.6	1 ks	


Nabídka 1 23001884 - 21.09.2023

Pol.	Produkt	Množství	Cena v EUR
2.0	PT R24 601 CMR 361, Active Capacitance Transmitter DN 16 ISO-KF 0,1 - 1100 mbar Accuracy: 0.2% of measurement Supply voltage: 18-30 V Output signal: 0- 10 V with integrated error signal Ceramic technology sensor: - no memory effects - excellent zero stability !!! ATTENTION !!! This pressure transducer to be shipped to you is subject to export controls (2B230, Annex I EG-Dual- use-VO). For the export of this good from the European Community an export license is necessary. *****	1 ks	
3.0	PE E50 100 0 OmniControl 200 - package Void - Gauge/IO - Void 100-240 V +/- 10 % Universal control device for all products with Pfeiffer Vacuum RS-485-Protocol Easy operation via 3.5" touch display Uncomplicated data collection and processing between the Pfeiffer Vacuum devices - Module Slot 2: Gauge/IO - Power consumption max.: 300 W - Output voltage: 24 V DC - Output current: 11.4 A	1 ks	
4.0	PT 448 250 -T Sensor cable CG for Single/Dual/MaxiGauge length: 3 m	1 ks	
5.0	B1913112SW Capillary 1/16 x 0,12 stainless steel	1.00 m	

Nabídka 1 23001884 - 21.09.2023

Pol.	Produkt	Množství	Cena v EUR
-------------	----------------	-----------------	-------------------


Should the costs underlying Pfeiffer Vacuum's calculation, in particular for personnel, material, raw materials, transport or energy - also due to exchange rate fluctuations - change by at least 5 % after conclusion of the contract, Pfeiffer Vacuum is entitled to adjust the price accordingly. The price adjustment shall be made in accordance with Pfeiffer Vacuum's calculation while maintaining the calculated profit. Pfeiffer Vacuum shall notify the customer of the price adjustment without undue delay and provide comprehensible reasons therefor. Insofar as the change in the underlying costs is due to a circumstance for which Pfeiffer Vacuum is responsible and which is contrary to the diligence of a prudent business practices, no price increase may be affected. In the event that a price increase exceeds 10 %, the customer shall have the option to cancel the relevant order free of charge for a period of two weeks from receipt of Pfeiffer Vacuum's notification. Such cancellation must be made in writing.

Ceny se rozumí "ex works", bez obalu a dopravného, bez DPH.
Obal, dopravné a pojistné jsou účtovány dle skutečných nákladů.
Pro nabídku a dodávku platí všeobecné dodací podmínky firmy PFEIFFER Vacuum GmbH dostupné na 

Doufáme, že nabídka odpovídá Vašim požadavkům a jsme připraveni poskytnout další doplňující informace.

Versicherung 

Fracht 

Verpackung 

Nabídka 1 23001884 - 21.09.2023

Pol.	Produkt	Množství	Cena v EUR
-------------	----------------	-----------------	-------------------

Daňový základ	3.894,66
DPH 0,0%	0,00
Celkem k platbě	3.894,66

Pfeiffer Vacuum Austria GmbH

Dodací podmínky: FCA

Doprava: UPS - United Parcel Service

Váha - Netto: 13,200

Platba: 30 dní po vystavení, netto

Bankovní spojení:

UniCredit Bank Austria AG

Erste Bank der Sparkassen AG

Swift/BIC:

BKAUATWW

GIBAATWW

Kód banky:

11000

20111

Číslo účtu:

09604401100

28319928000

IBAN:

AT971100009604401100

AT922011128319928000



High and Ultra-High Vacuum Isolation Valves

- Large range of angle valves with different actuator types
- Many variants available from stock
- Also available for order via Select & Request

— Anzeige / Advert —

