

To : Centrum výzkumu Řež s.r.o.
Objekt G2
Morseova 1245/6
301 00 Plzeň

Date : pátek 26. května 2017
Quotation No : OIVPG2102B

Your Ref :

For the Attention of : Josef Strejcius

Qty	Cat No	Description	Price
		Ave2	
1	2663-901	Advanced Video Extensometer 2 (AVE 2) Includes the extensometer, electronics, 2D calibration fixture, gauge mark template, and marker pens. Requires the selection of one mounting, one system interface, one or more lenses, one illumination bar, and one DIC option. Note - AVE2 is not compatible with 2910-062 or 2910-074 Debris Shield.	
1	2663-901T1	Transverse Strain Measurement Option Static transverse measurement option for use with Bluehill or as an analog output signal.	
1	2663-901R3	Licensed copy of DIC Replay Note: Requires the use of BH3.62 or higher on an Instron frame. Not for use on non-Instron test frames. Instron strongly recommends either: 1) a PC mouse (not included) when used with Bluehill Universal Operator Dashboard or 2) a separate PC for DIC data analysis.	
1	2663-901J1	Standard - Illumination kit for FOVs less than or equal to 250 mm	
1	2663-901P3	Continental Europe, Korea - Euro CEE7/7 (Hybrid Type E/F)	
1	2663-901D1	Short Field of View Lens - 35 mm Focal Length 100 mm FOV on Table (standard width) models, Single columns, ElectroPuls & 8800 130 mm fov on standard width floor models 170 mm FOV on heavyweight frames (5988 & 5989)	
1	2663-901C3	Interface and cables for systems that require a BNC analog connection. Note: 8800T and 8800D systems require an additional BNC to Instron connector cable (cat. no. 2210-877) and strain data acquisition channel (cat. no. 8800-612).	
1	2663-901BD	ElectroPuls - E3000, E10000 & Servohydraulic - 8870 - No Chamber - Mounting Mounts directly to the base and test frame column. Extensometer is positioned at 30 degrees to the loadstring for ambient testing. Suitable for both static and dynamic testing.	

Qty	Cat No	Description	Price
1	2663-901AB	Czech language option	
1	2210-877	Sensor Conditioner Adapter Cable, BNC sensor to 25 pin conditioner card. Adapts high level (+/- 10 V) transducers to Model 3300, 4400, 5500, 5800, 5900, Series, 8800, and ISRS Systems.	
		Note: System must have appropriate sensor card (not included).	
		Ex Works	1 423 590,00
1		Export Packing, Handling & FOB charges	7 000,00

TOTAL DAP Plzeň: 1.430.590 ,- CZK

Sleva pro CV Řež: 31.000,- CZK

Total DAP Plzeň: 1.399.590,- CZK

(Prices are without VAT)

TERMS AND CONDITIONS

VALIDITY OF QUOTE

90 days

DELIVERY

up to 20 days from purchase order

INSTALLATION

Igitur's engineer will then complete the connection of the services to the system, check that the system is working to specification and that all the components that make up the system order have been delivered and are in full working order. Training is at the price at required length.

SERVICE & SUPPORT

Igitur's office will provide service.

FAST SPARES

Igitur has an agreement with Instron and DHL Courier for the fast delivery of spare parts.

WARRANTY

12 months after installation and acceptance protocoll.

PAYMENT TERMS

100% Within 30days after installation

Vítězslav Hajný

Instron Limited