

## Příloha č. 1 – Technická specifikace

### Místnost 1

	S1	S2,S4	S3,S5	M1	M2-M8	Celkem
	1ks	2ks	2ks	1ks	7ks	
<b><u>Rám POZINK</u></b>						
2775x350	5	6	9			<b>20</b>
2625x350				6	42	<b>48</b>
2625x350 - PLNÝ				2	14	<b>16</b>
Čelo pro rám 2625x350						
<b><u>Police POZINK</u></b>						
970x350 N; 99kg krycí			6			<b>6</b>
1170x350 N; 68kg krycí	4	3		6	42	<b>55</b>
970x350 1R; 160kg			36			<b>36</b>
Výztuha 970 mm						
1170x350 2R; 145kg	24	18		36	252	<b>330</b>
Výztuha 1170 mm						
X - do pole	4	4	4	2	14	<b>28</b>
X - do rámu	6	12	12	8	56	<b>94</b>
<b><u>Podvozek RAL7021</u></b>						
3640x710 1x dělený					8	<b>8</b>
Koleje					23,00	<b>23</b>
Nášlap					46,00	<b>46</b>

**Místnost 2**

	S1	S2,S4	S3,S5	M1	M2- M8	Celkem
	1ks	2ks	2ks	1ks	7ks	
<b><u>Rám POZINK</u></b>						
2775x350	6	6	9			<b>21</b>
2625x350				8	56	<b>64</b>
2625x350 - PLNÝ				2	14	<b>16</b>
Čelo pro rám 2625x350						
<b><u>Police POZINK</u></b>						
1070x350 N; 77kg krycí	5		6	8	56	<b>75</b>
1170x350 N; 68kg krycí		3				<b>3</b>
1070x350 1R; 140kg	30		36	48	336	<b>450</b>
Výztuha 1070 mm						
1170x350 2R; 145kg		18				<b>18</b>
Výztuha 1170 mm						
X - do pole	4	4	4	4	28	<b>44</b>
X - do rámu	6	12	12	12	84	<b>126</b>
<b><u>Podvozek RAL7021</u></b>						
4440x710 1x dělený					8	<b>8</b>
Koleje					23,00	<b>23</b>
Nášlap					46,00	<b>46</b>