



## **Taraflex® Bateco**

Moveable protective layer

**Gerflor®**



# Protect your sport hall for extra sport use

Taraflex® Bateco is the ideal moveable solution for protecting sport floors during non-sporting activities. It can be unrolled over floors and then rolled up again before resuming sports activities.



Efficient protection of the sport flooring



Sustainable protective solution



Easy to install and to remove for multiple uses



Specific range of equipment available

## BATECO INSTALLED ON HARDWOOD SUBFLOOR



Made of 100% post-manufacturing waste



100% recyclable

MADE IN FRANCE



Antibacterial environments



TVOC emissions below detection level  
(TVOC <100µg/m3 after 28 days)

# Taraflex® Bateco Moveable protective layer



1 Special protective grain  
Black: masking sober colour



Thin layer with special protective grain prevents marks and stains, easy maintenance



Customizable length every 0,5 lm from 12 lm to 45 lm  
Width: 1,5 m



Outstanding fire resistance  
Bfl-S1



Looselay and edge-to-edge installation: can be secured with single-sided tape adhesive

## WIDE RANGE OF ACCESSORIES TO EASE THE INSTALLATION

MOBILE OR STATIC  
STORAGE RACKS




SINGLE-SIDED TAPE AND  
UNROLLER



SERVING TROLLEYS



DESCRIPTION	STANDARD	REQUIREMENT	UNITS	TARAFLEX® BATECO
<b>PRODUCT DESCRIPTION</b>				
Surface treatment	-	-	-	-
Surface complex	-	-	-	-
Foam	-	-	-	-
Thickness	EN ISO 24346 (EN 428)	-	mm	1,5
Weight	EN ISO 23997 (EN 430)	-	kg/m <sup>2</sup>	2,5
Length	EN ISO 24341 (EN 426)	-	ml	45 Max
Width	EN ISO 24341 (EN 426)	-	ml	1,5
<b>TECHNICAL CHARACTERISTICS</b>				
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 300
Impact resistance	EN 1517	≥ 8	N/m	-
Indentation resistance	EN 1516	≤ 0,5	mm	≤ 0,5
Dimensional stability	EN ISO 23999	-	%	1
<b>CLASSIFICATION</b>				
Fire	EN 13501-1	-	-	B <sub>f1</sub> -s1
Anti-bacterial activity (E. coli - S. aureus - MRSA) <sup>(1)</sup>	ISO 22196	-	-	> 99 % inhibits growth
<b>CE MARKING</b>				
	EN 14041	-	-	Fire
<b>INSTALLATION METHODS</b>				
	GERFLOR'S RECOMMENDATION		UNITS	RESULTS
LOOSE LAY ON THE EXISTING FLOORING	-		-	-

(1) The implementation of an effective cleaning method is the best defence against infection

## We care / we act Our Commitments for a Sustainable future

  
**CARBON FOOTPRINT\***  
 -20 % kg  
 CO<sub>2</sub> equivalent/m<sup>2</sup>  
 between 2020 and 2025

  
**BIOSOURCED CONTENT\*\***  
 10 % by 2025

  
**RECYCLED CONTENT**  
 30 % by 2025

  
**ADHESIVE FREE\*\*\***  
 35 % by 2025

  
**ANNUAL VOLUME RECYCLED**  
 60 000 t by 2025

**Gerflor®**

\* Scopes 1 and 2 defined in the GHG protocol \*\* % of activity with biosourced materials \*\*\* % of activity - adhesive free solution