

id.	VZT	velikost	výrobní číslo	množství vzduchu	externí tlaková ztráta	motor		napětí	In:	klinový řemen	předfiltr	filtr	topné médium	topný výkon	chladicí médium	chadičí výkon
1	1	HL 2	6635	3000 m³ / h	200 Pa	0.55 kW	2800 min-1	230 / 400 V, D / Y	1.36 A	1 ks SPZ 775 La	-	G4 - 360	voda 80 / 60 °C	9 kW	R 407 C	6.3 kW
2	1	HL 2	6635	1400 m³ / h	200 Pa	0.55 kW	2800 min-1	230 / 400 V, D / Y	1.36 A	1 ks SPZ 800 La	-					
3	2	HL 3.15	6626	3000 m³ / h	270 Pa	1.5 / 1.9 kW	1390 / 2845 min-1	400 V, D / YY	3.4 / 4.5 A	2 ks SPZ 900 La	-	G4 - 360	voda 80 / 60 °C	17.1 kW	R 407 C	14.1 kW
4	2	HL 3.15	6626	3000 m³ / h	250 Pa	1.1 / 1.4 kW	1390 / 2810 min-1	230 / 400 V, D / Y	2.7 / 3.6 A	1 ks SPZ 950 La	-					
5	3	H 2	6627	2100 m³ / h	270 Pa	1.5 / 1.9 kW	1390 / 2845 min-1	400 V, D / YY	3.4 / 4.5 A	2 ks SPZ 825 La	-	G4 - 360	voda 80 / 60 °C	13.4 kW	R 407 C	12.6 kW
6	3	H 2	6627	2000 m³ / h	220 Pa	1.1 / 1.4 kW	1390 / 2810 min-1	230 / 400 V, D / Y	2.7 / 3.6 A	1 ks SPZ 850 La	-					
7	4	H 2.5	6628	2500 m³ / h	230 Pa	1.5 / 1.9 kW	1390 / 2845 min-1	400 V, D / YY	3.4 / 4.5 A	2 ks SPZ 800 La	-	G4 - 360	voda 80 / 60 °C	15.1 kW	R 407 C	12.6 kW
8	4	H 2.5	6628	2500 m³ / h	200 Pa	1.1 / 1.4 kW	1390 / 2810 min-1	230 / 400 V, D / Y	2.7 / 3.6 A	1 ks SPZ 825 La	-					
9	5	H 2	6629	2100 m³ / h	270 Pa	1.5 / 1.9 kW	1390 / 2845 min-1	400 V, D / YY	3.4 / 4.5 A	2 ks SPZ 775 La	-	G4 - 360	voda 80 / 60 °C	13.4 kW	R 407 C	12.6 kW
10	5	H 2	6629	2000 m³ / h	220 Pa	1.1 / 1.4 kW	1390 / 2810 min-1	230 / 400 V, D / Y	2.7 / 3.6 A	1 ks SPZ 850 La	-					
11	6	H 2.5	6630	2600 m³ / h	280 Pa	1.5 / 1.9 kW	1390 / 2845 min-1	400 V, D / YY	3.4 / 4.5 A	2 ks SPZ 825 La	-	G4 - 360	voda 80 / 60 °C	15.7 kW	R 407 C	13.7 kW
12	6	H 2.5	6630	2600 m³ / h	240 Pa	1.5 / 1.9 kW	1390 / 2845 min-1	400 V, D / YY	3.4 / 4.5 A	2 ks SPZ 825 La	-					
13	7	H 2	6631	2100 m³ / h	270 Pa	1.1 / 1.4 kW	1390 / 2810 min-1	230 / 400 V, D / Y	2.7 / 3.6 A	1 ks SPZ 825 La	-	G4 - 360	voda 80 / 60 °C	13.4 kW	R 407 C	12.6 kW
14	7	H 2	6631	2100 m³ / h	240 Pa	1.1 / 1.4 kW	1390 / 2810 min-1	230 / 400 V, D / Y	2.7 / 3.6 A	1 ks SPZ 875 La	-					
15	8	H 3.15	6632	3000 m³ / h	320 Pa	2 / 2.4 kW	1400 / 2850 min-1	400 V, D / YY	4.3 / 5.7 A	2 ks SPZ 950 La	-	G4 - 360	voda 80 / 60 °C	17.7 kW	R 407 C	15.5 kW
16	8	H 3.15	6632	3000 m³ / h	320 Pa	1.5 / 1.9 kW	1390 / 2845 min-1	400 V, D / YY	3.4 / 4.5 A	1 ks SPZ 1100 La	-					
17	9	H 2	6633	2100 m³ / h	260 Pa	1.1 / 1.4 kW	1390 / 2810 min-1	230 / 400 V, D / Y	2.7 / 3.6 A	2 ks SPZ 800 La	-	G4 - 360	voda 80 / 60 °C	13.4 kW	R 407 C	12.6 kW
18	9	H 2	6633	2000 m³ / h	220 Pa	0.7 / 0.85 kW	1390 / 2810 min-1	400 V, D / YY	1.75 / 2.1 A	1 ks SPZ 850 La	-					
19	10	H 4	6634	4400 m³ / h	320 Pa	2.6 / 3.1 kW	1400 / 2850 min-1	400 V, D / YY	5.5 / 7.6 A	2 ks SPZ 975 La	-	G4 - 360	voda 80 / 60 °C	29.5 kW	R 407 C	22.4 kW
20	10	H 4	6634	4400 m³ / h	230 Pa	1.8 / 3.6 kW	720 / 1430 min-1	400 V, D / YY	6.3 / 7.2 A	3 ks SPZ 1075 La	-					
21	11	H 2	6625	1600 m³ / h	220 Pa	0.7 / 0.85 kW	1390 / 2810 min-1	400 V, D / YY	1.75 / 2.1 A	1 ks SPZ 825 La	-	G4 - 360	voda 80 / 60 °C	9.6 kW	R 407 C	6.3 kW
22	11	H 2	6625	1800 m³ / h	220 Pa	0.7 / 0.85 kW	1390 / 2810 min-1	400 V, D / YY	1.75 / 2.1 A	1 ks SPZ 775 La	-					

FLTRY	27
KS PAK 35 395 x 195 x 420	4
KS PAK 35 402 x 402 x 360	10
KS PAK 35 490 x 490 x 360	6
KS PAK 35 497 x 292 x 420	1
KS PAK 35 592 x 287 x 360	2
KS PAK 35 592 x 592 x 360	2
KS PAK 35 734 x 430 x 360	2
	0

Příloha č. 3 rámcové dohody - Technická specifikace zařízení VZT - POBOČKA OLOMOUC