

List of National / Default Data / Seznam národních /defaultních hodnot

National / Default Data	National Value	Default Value	SRS Name (Reference only)
Modification of adhesion factor by driver	Allowed	Not allowed	Q_NVDRIVER_ADHES
Shunting mode (permitted) speed limit	40 km/h	30 km/h	V_NVSHUNT
Staff Responsible mode (permitted) speed limit	40 km/h	40 km/h	V_NVSTFF
On Sight mode (permitted) speed limit	100 km/h	30 km/h	V_NVONSIGHT
Unfitted mode (permitted) speed limit	100 km/h	100 km/h	V_NVUNFIT
Release Speed value	40 km/h	40 km/h	V_NVREL
Distance to be used in Roll Away protection, Reverse movement protection and Standstill supervision	8 m	2 m	D_NVROLL
Use service brake when braking to a target	Yes	Yes	Q_NVSRBKTRG
Permission to release emergency brake	Immediate release possible	Only at standstill	Q_NVEMRRLS
Max. speed limit for triggering the override end of authority function	40 km/h	0 km/h	V_NVALLOWOVTRP
Permitted speed limit to be supervised when the "override EOA" function is active	40 km/h	30 km/h	V_NVSUPOVTRP
Distance for train trip suppression when override end of authority function is triggered	200 m	200 m	D_NVOVTRP
Max. time for train trip suppression when override end of authority function is triggered	60 s	60 s	T_NVOVTRP
Change of driver ID permitted while running	No	Yes	M_NVDERUN
System reaction if radio channel monitoring time limit expires (T-Contact)	SB	No reaction	M_NVCONTACT
Maximum time since creation in the RBC of last received telegram.	180 s	∞	T_NVCONTACT
Distance to be allowed for reversing in Post Trip mode.	8 m	200 m	D_NVPOTRP
Max permitted distance to run in Staff Responsible mode	∞	∞	D_NVSTFF

List of SŽDC Data / Seznam SŽDC dat

SŽDC Data	Value	Possibility of change by customer	Name
STM (permitted) speed limit	160 km/h	No	CZ_V_STMLS
LX failure (permitted) speed limit	10 km/h	Can be	CZ_V_LXF
Distance to be used for LX failure (permitted) speed limit	60 m	Can be	CZ_D_LXF
Distance to be used for Text message for LX failure	500 m	Can be	CZ_D_TMLXF
Distance for sending TSR for LX failure for OBU in SR	1500 m	Yes	CZ_D_LXFSR
Distance to be used for Text message for signal failure	500 m	Can be	CZ_D_TMSF
Speed limit for transition to OS in rear of the signal Permissive red	40 km/h	Yes	CZ_V_OSPERMISR
Distance to be used for OS in rear of the signal with Permissive red	300 m	Yes	CZ_D_OSPERMISR
Speed limit for transition to OS in rear of Absolute red	40 km/h	Yes	CZ_V_OSABSOLR
Distance to be used for OS in rear of the signal with absolute red	300 m	Yes	CZ_D_OSABSOLR
Speed limit for transition to OS at the platform during run to occupied station track	20 km/h	Yes	CZ_V_OSPLAT
Speed limit for OS on call-on aspect in the LX approach area in the station (in the departure route up to the end of the outside switch point) – it is valid only for front end of the train	40 km/h	No	CZ_V_OSSTALX
Speed limit for OS on call-on aspect in the switch point area (excluding of the running in the straight direction) – it is valid only for front end of the train	40 km/h	Yes	CZ_V_OSSWITCH
Speed limit for exclusion of TZZ	100 km/h	Yes	CZ_V_EXCLTZZ
Distance to be used for maximum TAF Request displaying on the DMI	500 m	Yes	CZ_D_TAFREQDISP
Distance to be used for Text message for run to a specific km on a plain track and backwards	500 m	Can be	CZ_D_TMRTKM
Tolerable of overspeed when the driver set the maximum max speed in SR more than value V_NVUNFIT	7,5 km/h	Yes	CZ_V_SRTOL
Speed limit can be higher than a signal aspect in some cases	No	Yes	CZ_Q_SPEEDHIGHSAS