

4.1 Nabízené konfigurace

4.1.1 Server 1

System: 1) 1ks PY RX2530 M4 4x 3.5'

Product no.	Name	Quantity
S26361-K1592-V101	PY RX2530 M4 4x 3.5' Rack server 19" (1U), Base unit with systemboard D3383-A for up to 2x Xeon DP processors and 24x DDR4 DIMM slots; iRMC S5 onboard server management incl. graphics controller; 10/100/1000MBit Service LAN port, LAN on Motherboard with 2x1Gbit/s (RJ45) plus the high performance Chip Intel LBG4 with flexible LAN connections - options for 4x1Gbit/s (RJ45), 2x10Gbit/s (RJ45), 2x10Gbit/s (SFP+) and 4x10Gbit/s (SFP+); RAID 0/1 6Gbit/s Controller onboard; 4 bays for hot plug 3,5" SAS/SATA drives; 4/8 single hot plug fans; ServerView Suite Software Pack optional The Systemarchitekt suggests 2x 450W hot plug power supplies per default. This is optimal for most configurations (in case of doubt, please check with the power calculator). Delivery in single packaging, minimum order quantity: 1 unit.	1
S26361-F4051-E110	Intel Xeon Silver 4110 8C 2.10 GHz	2
S26361-F3849-E100	Cooler Kit 2nd CPU	1
S26361-F3694-E10	Independent Mode Installation	2
S26361-F4026-E216	16GB (1x16GB) 1Rx4 DDR4-2666 R ECC	2
S26361-F5568-E130	HD SAS 12G 300GB 10K 512n HOT PL 3.5' EP	4
S26361-F3842-E1	PRAID CP400i	1
S26361-F3953-E100	PLAN EM Blind Panel OCP	1
S26361-F2735-E400	Rack Mount Kit F1-CMA Slim Line	1
S26361-F4530-E10	Mounting of RMK in symmetrical racks	1
S26361-F2735-E81	Rack Cable Arm 1U	1
S26361-F1452-E140	Region-kit Europe	1
S26361-F2036-E100	ServerView Suite DVDs	1
S26361-F1790-E311	eLCM Activation License	1
S26361-F1790-E243	iRMC advanced pack	1
S26113-F575-E13	Modular PSU 450W platinum hp	2
T26139-Y1968-E250	Cable powercord rack, 2.5m, black	2
FSP:GB3S20Z00CZSV2	SP 3y OS,9x5,NBD Rt	1

4.1.2 Server 2

System: 2) 1ks PY RX2530 M4 4x 3.5'

Product no.	Name	Quantity
S26361-K1592-V101	PY RX2530 M4 4x 3.5'	1
	<p>Rack server 19" (1U), Base unit with systemboard D3383-A for up to 2x Xeon DP processors and 24x DDR4 DIMM slots; iRMC S5 onboard server management incl. graphics controller; 10/100/1000MBit Service LAN port, LAN on Motherboard with 2x1Gbit/s (RJ45) plus the high performance Chip Intel LBG4 with flexible LAN connections - options for 4x1Gbit/s (RJ45), 2x10Gbit/s (RJ45), 2x10Gbit/s (SFP+) and 4x10Gbit/s (SFP+); RAID 0/1 6Gbit/s Controller onboard; 4 bays for hot plug 3,5" SAS/SATA drives; 4/8 single hot plug fans; ServerView Suite Software Pack optional The Systemarchitekt suggests 2x 450W hot plug power supplies per default. This is optimal for most configurations (in case of doubt, please check with the power calculator). Delivery in single packaging, minimum order quantity: 1 unit.</p> <p>Standard warranty: 3 years, On-Site Service, 5 days / 9 hours (5x9, local business hours), FTS wide / FTS</p>	
S26361-F4051-E110	Intel Xeon Silver 4110 8C 2.10 GHz	2
S26361-F3849-E100	Cooler Kit 2nd CPU	1
S26361-F3694-E10	Independent Mode Installation	2
S26361-F4026-E232	32GB (1x32GB) 2Rx4 DDR4-2666 R ECC	4
S26361-F5568-E130	HD SAS 12G 300GB 10K 512n HOT PL 3.5' EP	4
S26361-F3842-E1	PRAID CP400i	1
S26361-F3953-E100	PLAN EM Blind Panel OCP	1
S26361-F2735-E400	Rack Mount Kit F1-CMA Slim Line	1
S26361-F4530-E10	Mounting of RMK in symmetrical racks	1
S26361-F2735-E81	Rack Cable Arm 1U	1
S26361-F1452-E140	Region-kit Europe	1
S26361-F2036-E100	ServerView Suite DVDs	1
S26361-F1790-E311	eLCM Activation License	1
S26361-F1790-E243	iRMC advanced pack	1
S26113-F575-E13	Modular PSU 450W platinum hp	2
T26139-Y1968-E250	Cable powercord rack, 2.5m, black	2
FSP:GB3S20Z00CZSV2	SP 3y OS,9x5,NBD Rt	1

4.1.3 Server 3

System: 3) 2ks PY RX2530 M4 4x 3.5'

Product no.	Name	Quantity
S26361-K1592-V101	PY RX2530 M4 4x 3.5'	1
	Rack server 19" (1U), Base unit with systemboard D3383-A for up to 2x Xeon DP processors and 24x DDR4 DIMM slots; iRMC S5 onboard server management incl. graphics controller; 10/100/1000MBit Service LAN port, LAN on Motherboard with 2x1Gbit/s (RJ45) plus the high performance Chip Intel LBG4 with flexible LAN connections - options for 4x1Gbit/s (RJ45), 2x10Gbit/s (RJ45), 2x10Gbit/s (SFP+) and 4x10Gbit/s (SFP+); RAID 0/1 6Gbit/s Controller onboard; 4 bays for hot plug 3.5" SAS/SATA drives; 4/8 single hot plug fans; ServerView Suite Software Pack optional The Systemarchitekt suggests 2x 450W hot plug power supplies per default. This is optimal for most configurations (in case of doubt, please check with the power calculator). Delivery in single packaging, minimum order quantity: 1 unit.	
S26361-F4051-E110	Intel Xeon Silver 4110 8C 2.10 GHz	2
S26361-F3849-E100	Cooler Kit 2nd CPU	1
S26361-F3694-E10	Independent Mode Installation	2
S26361-F4026-E232	32GB (1x32GB) 2Rx4 DDR4-2666 R ECC	2
S26361-F5568-E130	HD SAS 12G 300GB 10K 512n HOT PL 3.5' EP	4
S26361-F3842-E1	PRAID CP400i	1
S26361-F3953-E100	PLAN EM Blind Panel OCP	1
S26361-F2735-E400	Rack Mount Kit F1-CMA Slim Line	1
S26361-F4530-E10	Mounting of RMK in symmetrical racks	1
S26361-F2735-E81	Rack Cable Arm 1U	1
S26361-F1452-E140	Region-kit Europe	1
S26361-F2036-E100	ServerView Suite DVDs	1
S26361-F1790-E311	eLCM Activation License	1
S26361-F1790-E243	iRMC advanced pack	1
S26113-F575-E13	Modular PSU 450W platinum hp	2
T26139-Y1968-E250	Cable powercord rack, 2.5m, black	2
FSP:GB3S20Z00CZSV2	SP 3y OS,9x5,NBD Rt	1

4.1.4 Poznámky k PCIe slotům

Slot 1 (interní): PCIe Gen3 x8 @CPU1 je vyhrazen pro modulární řadič RAID.

Slot 2: PCIe Gen3 x16 @CPU1 pro nízké karty s délkou až 167 mm

Slot 3: PCIe Gen3 x16 @CPU1 pro nízké karty s délkou až 167 mm

Slot 4 (standardně): PCIe Gen3 x16 @CPU2 pro nízké karty s délkou až 167 mm

Slot 4 (volitelně): PCIe Gen3 x16 @CPU2 pro karty s plnou výškou a délkou až 167 mm (v tomto případě není k dispozici slot 3)

Jsou požadovány minimálně 2 PCIe sloty my nabízíme 3