

Odběratel: **FYZIKÁLNÍ ÚSTAV AV ČR, v.v.i.****Na Slovance 2
182 21 PRAHA 8
Česká republika**

PID:

Smlouva: **S17/164E**

Číslo účtu:

Peněžní ústav:

DIČ: **CZ68378271**
IČ: **68378271**

Dodavatel:

IČ: **46348395** DIČ: **CZ46348395**

Doručovací adresa

**Fyzikální ústav AV ČR, v. v. i. -
ELI Beamlines - sklad,
Průmyslová 836, 25241 Dolní
Břežany****020931 RP3 Elimaia****Ing. Urbanec Andrej**

Tel.: , Fax:

Způsob dopravy : **včetně dopravy**Dodací podmínky : **DAP Praha****MIT, spol. s r.o.
Lasery, fotonika a jemná mechanika
Klánova 56
PRAHA 4
Česká republika**Platnost objednávky do: **31.12.2018**Termín dodání: **24.07.2018**Forma úhrady: **Příkazem**Termín úhrady: **21 dni****!!!! Při fakturaci vždy uvádějte číslo objednávky !!!!****Žádáme Vás o potvrzení objednávky.**

MN10858 - Z důvodu uznatelnosti nákladů musí být na faktuře uvedeno číslo objednávky, číslo projektu CZ.02.1.01/0.0/0.0/15_008/0000162 a název projektu ELI - EXTREME LIGHT INFRASTRUCTURE - fáze 2, v opačném případě bude faktura vrácena.

Položkový rozpis:

Nedílnou součástí této objednávky je příloha obsahující řádky.**Předpokládaná cena celkem (včetně DPH):****2 314 313.76 Kč****Datum vystavení: 12.06.2018****Vystavil:**

Ing. Urbanec Andrej

E-mail: andrej.urbanec@eli-beams.eu

Razítko, podpis

Položka	Množství	MJ	Cena/MJ vč. DPH	Celkem s DPH
3 Protected silver coating mirror 1" Eksma Optics 092-3025 (mod.) Substrate fused silica. Diameter=1", Diameter tolerance +0.0 mm / -0.1 mm. Thickness 6 mm, Thickness tolerance ?0.2 mm. Surface flatness ?/10. Protected silver coating. Clear aperture > 90%	20.00	ks	915.00	18 300.00 Kč
4 Protected silver coating mirror 2" Thorlabs PF20-03-P01 Substrate fused silica. Diameter=2", Diameter tolerance +0.0 mm / -0.1 mm. Thickness 12 mm, Thickness tolerance ?0.2 mm. Surface flatness ?/10. Protected silver coating. Clear aperture > 90% of dia	20.00	ks	2 475.00	49 500.00 Kč
5 Protected silver coating mirror 4" Eksma Optics 095-3025 (mod.) Substrate fused silica. Diameter=4", Diameter tolerance +0.0 mm / -0.1 mm. Thickness 19.1 mm, Thickness tolerance ?0.2 mm. Surface flatness ?/10. Protected silver coating. Clear aperture >	4.00	ks	9 030.00	36 120.00 Kč
12 Dielectric coating mirror 1" Altechna 1-OS-1-0254-6-[2B45] Diameter=1?; Diameter Tolerance: +0/?0.25 mm; Wavelength range 720 ? 880 nm; Substrate Material: UV grade Fused Silica; Surface flatness: ?/10 @ 633 nm; Surface Quality: 20-10 scratch and di	10.00	ks	1 643.00	16 430.00 Kč
13 Dielectric coating mirror 2" Altechna 1-OS-1-0508-8-[2B45] Diameter=2?; Diameter Tolerance: +0/?0.25 mm; Wavelength range 720 ? 880 nm; Substrate Material: UV grade Fused Silica; Surface flatness: ?/10 @ 633 nm; Surface Quality: 20-10 scratch and di	10.00	ks	3 013.00	30 130.00 Kč
14 Dielectric coating mirror 4" Eksma Optics 088-7288 Diameter=4?; Diameter Tolerance: +0/?0.25 mm; Wavelength range 720 ? 880 nm; Substrate Material: UV grade Fused Silica; Surface flatness: ?/10 @ 633 nm; Surface Quality: 20-10 scratch and dig; Thicknes	4.00	ks	22 141.00	88 564.00 Kč
15 Dielectric coating mirror 1" Altechna CM-1-OS-1-0254-6-[2B00] Diameter=1?; Diameter Tolerance: +0/?0.25 mm; Wavelength range 720 ? 880 nm; Substrate Material: UV grade Fused Silica; Surface flatness: ?/10 @ 633 nm; Surface Quality: 20-10 scratch	2.00	ks	1 715.00	3 430.00 Kč
16 Dielectric coating mirror 2" Altechna CM-1-OS-1-0508-8-[2B00] Diameter=2?; Diameter Tolerance: +0/?0.25 mm; Wavelength range 720 ? 880 nm; Substrate Material: UV grade Fused Silica; Surface flatness: ?/10 @ 633 nm; Surface Quality: 20-10 scrat	2.00	ks	3 145.00	6 290.00 Kč
21 Achromatic doublet lens 1" Thorlabs AC254-400-B Focal length: 400 mm; Design Wavelengths: 855 nm; AR Coating Range: 650 - 1050 nm; Reflectance over AR Coating Range (0° AOI) Ravg < 0.5%; Diameter 1"; Diameter Tolerance:+0.00/-0.10 mm; Focal Length	3.00	ks	2 165.00	6 495.00 Kč
22 Achromatic doublet lens 1" Thorlabs AC254-500-B Focal length: 500 mm; Design Wavelengths: 855 nm; AR Coating Range: 650 - 1050 nm; Reflectance over AR Coating Range (0° AOI) Ravg < 0.5%; Diameter 1"; Diameter Tolerance:+0.00/-0.10 mm; Focal Length	3.00	ks	2 165.00	6 495.00 Kč
23 Achromatic doublet lens 2" Thorlabs AC508-100-B Focal length: 100 mm; Design Wavelengths: 855 nm; AR Coating Range: 650 - 1050 nm; Reflectance over AR Coating Range (0° AOI) Ravg < 0.5%; Diameter 2"; Diameter Tolerance:+0.00/-0.10 mm; Focal Length	3.00	ks	3 267.00	9 801.00 Kč
24 Achromatic doublet lens 2" Thorlabs AC508-200-B Focal length: 200 mm; Design Wavelengths: 855 nm; AR Coating Range: 650 - 1050 nm; Reflectance over AR Coating Range (0° AOI) Ravg < 0.5%; Diameter 2"; Diameter Tolerance:+0.00/-0.10 mm; Focal Length	3.00	ks	3 267.00	9 801.00 Kč
25 Achromatic doublet lens 2" Thorlabs AC508-300-B Focal length: 300 mm; Design Wavelengths: 855 nm; AR Coating Range: 650 - 1050 nm; Reflectance over AR Coating Range (0° AOI) Ravg < 0.5%; Diameter 2"; Diameter Tolerance:+0.00/-0.10 mm; Focal Length	3.00	ks	3 267.00	9 801.00 Kč
26 Achromatic doublet lens 2" Thorlabs AC508-400-B Focal length: 400 mm; Design Wavelengths: 855 nm; AR Coating Range: 650 - 1050 nm; Reflectance over AR Coating Range (0° AOI) Ravg < 0.5%; Diameter 2"; Diameter Tolerance:+0.00/-0.10 mm; Focal Length	3.00	ks	3 267.00	9 801.00 Kč
27 Achromatic doublet lens 2" Thorlabs AC508-500-B Focal length: 500mm; Design Wavelengths: 855 nm; AR Coating Range: 650 - 1050 nm; Reflectance over AR Coating Range (0° AOI) Ravg < 0.5%; Diameter 2"; Diameter Tolerance:+0.00/-0.10 mm; Focal Length T	3.00	ks	3 267.00	9 801.00 Kč
28 Achromatic doublet lens 2" Thorlabs AC508-750-B Focal length: 750 mm; Design Wavelengths: 855 nm; AR Coating Range: 650 - 1050 nm; Reflectance over AR Coating Range (0° AOI) Ravg < 0.5%; Diameter 2"; Diameter Tolerance:+0.00/-0.10 mm; Focal Length Tole	3.00	ks	3 267.00	9 801.00 Kč

Žádáme Vás o zaslání daňových dokladů v elektronické podobě (skeny) na adresu efaktury@fzu.cz. O doručení dokladů obdržíte potvrzující e-mail. Objednávku nad 50 000 Kč uveřejníme v souladu se zákonem č. 340/2015 Sb., o zvláštních podmínkách účinnosti některých smluv, uveřejňování těchto smluv a o registru smluv, v platném znění.

Položka				
	Množství	MJ	Cena/MJ vč. DPH	Celkem s DPH
29 Achromatic doublet lens 2" Thorlabs AC508-1000-B Focal length: 1000 mm; Design Wavelengths: 855 nm; AR Coating Range: 650 - 1050 nm; Reflectance over AR Coating Range (0° AOI) Ravg < 0.5%; Diameter 2"; Diameter Tolerance: +0.00/-0.10 mm; Focal Length To	3.00	ks	3 267.00	9 801.00 Kč
30 Cube Polarizers Thorlabs PBS252 Dimensions 1.0" x 1.0" x 1.0". Thickness Tolerance ?0.254 mm. Broadband coating 620 - 1000 nm. Polarizer cube separation angle 90°. Surface Accuracy ??/4 at 632.8 nm over the clear aperture. AR coating on the 4 faces.	3.00	ks	5 391.00	16 173.00 Kč
32 Neutral density filter 1" Altechna 1-NF-01-0254 (mod.) OD=0.1; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?/4; Surface Quality: 40-20 Scratch-Dig	3.00	ks	1 143.00	3 429.00 Kč
33 Neutral density filter 1" Altechna 1-NF-03-0254 (mod.) OD=0.3; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?/4; Surface Quality: 40-20 Scratch-Dig	5.00	ks	1 143.00	5 715.00 Kč
34 Neutral density filter 1" Altechna 1-NF-05-0254 (mod.) OD=0.5; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?/4; Surface Quality: 40-20 Scratch-Dig	5.00	ks	1 143.00	5 715.00 Kč
35 Neutral density filter 1" Altechna 1-NF-10-0254 (mod.) OD=1; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?/4; Surface Quality: 40-20 Scratch-Dig;	5.00	ks	1 143.00	5 715.00 Kč
36 Neutral density filter 1" Altechna 1-NF-20-0254 (mod.) OD=2; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?/4; Surface Quality: 40-20 Scratch-Dig;	5.00	ks	1 143.00	5 715.00 Kč
37 Neutral density filter 1" Altechna 1-NF-30-0254 (mod.) OD=3; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?/4; Surface Quality: 40-20 Scratch-Dig;	4.00	ks	1 143.00	4 572.00 Kč
38 Neutral density filter 1" Altechna 1-NF-40-0254 (mod.) OD=4; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?/4; Surface Quality: 40-20 Scratch-Dig;	4.00	ks	1 143.00	4 572.00 Kč
39 Neutral density filter 1" Altechna 1-NF-50-0254 (mod.) OD=5; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?/4; Surface Quality: 40-20 Scratch-Dig;	3.00	ks	1 143.00	3 429.00 Kč
40 Neutral density filter 1" Altechna 1-NF-50-0254 (mod.) OD=6; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?/4; Surface Quality: 40-20 Scratch-Dig;	3.00	ks	1 143.00	3 429.00 Kč
41 Neutral density filter 2" Altechna 1-NF-01-0505 (mod.) OD=0.1; Diameter=2"; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?; Surface Quality: 40-20 Scratch-Dig; Parall	2.00	ks	1 687.00	3 374.00 Kč
42 Neutral density filter 2" Altechna 1-NF-03-0505 (mod.) OD=0.3; Diameter=2"; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?; Surface Quality: 40-20 Scratch-Dig; Parall	3.00	ks	1 687.00	5 061.00 Kč
43 Neutral density filter 2" Altechna 1-NF-05-0505 (mod.) OD=0.5; Diameter=2"; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?; Surface Quality: 40-20 Scratch-Dig; Parall	5.00	ks	1 687.00	8 435.00 Kč
44 Neutral density filter 2" Altechna 1-NF-10-0505 (mod.) OD=1; Diameter=2"; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?; Surface Quality: 40-20 Scratch-Dig; Parallel	5.00	ks	1 687.00	8 435.00 Kč
45 Neutral density filter 2" Altechna 1-NF-20-0505 (mod.) OD=2; Diameter=2"; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?; Surface Quality: 40-20 Scratch-Dig; Parallel	5.00	ks	1 687.00	8 435.00 Kč
46 Neutral density filter 2" Altechna 1-NF-30-0505 (mod.) OD=3; Diameter=2"; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?; Surface Quality: 40-20				

Zádáme Vás o zaslání daňových dokladů v elektronické podobě (skeny) na adresu efaktury@fzu.cz. O doručení dokladů obdržíte potvrzující e-mail. Objednávku nad 50 000 Kč uveřejníme v souladu se zákonem č. 340/2015 Sb., o zvláštních podmínkách účinnosti některých smluv, uveřejňování těchto smluv a o registru smluv, v platném znění.

Položka	Množství	MJ	Cena/MJ vč. DPH	Celkem s DPH
Scratch-Dig; Paralel	4.00	ks	1 687.00	6 748.00 Kč
47 Neutral density filter 2" Altechna 1-NF-40-0505 (mod.) OD=4; Diameter=2"; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?; Surface Quality: 40-20 Scratch-Dig; Paralel	4.00	ks	1 687.00	6 748.00 Kč
48 Neutral density filter 2" Altechna 1-NF-50-0505 (mod.) OD=5; Diameter=2"; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?; Surface Quality: 40-20 Scratch-Dig; Paralel	4.00	ks	1 687.00	6 748.00 Kč
49 Neutral density filter 2" Altechna 1-NF-60-0505 (mod.) OD=6; Diameter=2"; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <0.5%; Surface Flatness (@ 633 nm): ?; Surface Quality: 40-20 Scratch-Dig; Paralel	3.00	ks	1 687.00	5 061.00 Kč
50 Neutral density filter 1"; AR-Coated Neutral Density Filter, 650-1050 nm Altechna "1-NF-01-0254 (mod.) + BBAR 1-OS-2-0254-5-[NIR]" OD=0.1; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm)	3.00	ks	1 143.00	3 429.00 Kč
51 Neutral density filter 1"; AR-Coated Neutral Density Filter, 650-1050 nm Altechna "1-NF-03-0254 (mod.) + BBAR 1-OS-2-0254-5-[NIR]" OD=0.3; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm):	3.00	ks	1 143.00	3 429.00 Kč
52 Neutral density filter 1"; AR-Coated Neutral Density Filter, 650-1050 nm Altechna "1-NF-05-0254 (mod.) BBAR 1-OS-2-0254-5-[NIR]" OD=0.5; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <	5.00	ks	1 143.00	5 715.00 Kč
53 Neutral density filter 1"; AR-Coated Neutral Density Filter, 650-1050 nm Altechna "1-NF-10-0254 (mod.) + BBAR 1-OS-2-0254-5-[NIR]" OD=1; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <	5.00	ks	1 143.00	5 715.00 Kč
54 Neutral density filter 1"; AR-Coated Neutral Density Filter, 650-1050 nm Altechna "1-NF-20-0254 (mod.) + BBAR 1-OS-2-0254-5-[NIR]" OD=2; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm):	5.00	ks	1 143.00	5 715.00 Kč
55 Neutral density filter 1"; AR-Coated Neutral Density Filter, 650-1050 nm Altechna "1-NF-30-0254 (mod.) + BBAR 1-OS-2-0254-5-[NIR]" OD=3; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <	4.00	ks	1 143.00	4 572.00 Kč
56 Neutral density filter 1"; AR-Coated Neutral Density Filter, 650-1050 nm Altechna "1-NF-40-0254 (mod.) + BBAR 1-OS-2-0254-5-[NIR]" OD=4; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm):	4.00	ks	1 143.00	4 572.00 Kč
57 Neutral density filter 1"; AR-Coated Neutral Density Filter, 650-1050 nm Altechna "1-NF-50-0254 (mod.) + BBAR 1-OS-2-0254-5-[NIR]" OD=5; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <	4.00	ks	1 143.00	4 572.00 Kč
58 Neutral density filter 1"; AR-Coated Neutral Density Filter, 650-1050 nm Altechna "1-NF-50-0254 (mod.) + BBAR 1-OS-2-0254-5-[NIR]" OD=6; Diameter: 25.0 mm; Diameter Tolerance: +0.5 / -0.25 mm; Clear Aperture: >90% Outer Diameter; Ravg (350 - 700 nm): <	4.00	ks	1 143.00	4 572.00 Kč
59 BeamSplitters 50/50, 2" Eksma Optics "220-0566E (mod.) + 2075-i45 (mod.)" Diameter=2". Split: T= 50%, R=50% , operating range 600 - 1000 nm. Thickness < 5 mm. Angle of incidence 45 deg. 20-10 scratch dig. Parallelism <5 arcmin. Surface flatness ?/4 o	5.00	ks	9 772.00	48 860.00 Kč
60 BeamSplitters 20/80, 2" Eksma Optics "220-0566E (mod.) + 2077-i47 (mod.)" Diameter=2". Split: T= 20%, R=80% , operating range 600 - 1000 nm. Thickness < 5 mm. Angle of incidence 45 deg. 20-10 scratch dig. Parallelism <5 arcmin. Surface flatness ?/4 or	2.00	ks	18 544.00	37 088.00 Kč
61 BeamSplitters 80/20, 2" Eksma Optics "220-0566E (mod.) + 2072-i45 (mod.)" Diameter=2". Split: T= 80%, R=20% , operating range 600 - 1000 nm. Thickness < 5 mm. Angle of incidence 45 deg. 20-10 scratch dig. Parallelism <5 arcmin. Surface flatness ?/4 or	2.00	ks	7 174.00	14 348.00 Kč
62 BeamSplitters 50/50, 2" Thorlabs BSW16 Split Ratio (R:T) 50:50; Diameter=2"; Diameter Tolerance +0.0 mm / - 0.2 mm; Center Thickness 8 mm; Thickness Tolerance ?0.4 mm; Surface Flatness (Peak to Valley) ?/10 @ 633 nm Over the Clear Aperture; Coating on				

Žádáme Vás o zaslání daňových dokladů v elektronické podobě (skeny) na adresu efaktury@fzu.cz. O doručení dokladů obdržíte potvrzující e-mail. Objednávku nad 50 000 Kč uveřejníme v souladu se zákonem č. 340/2015 Sb., o zvláštních podmínkách účinnosti některých smluv, uveřejňování těchto smluv a o registru smluv, v platném znění.

Položka		Množství	MJ	Cena/MJ vč. DPH	Celkem s DPH
63	BeamSplitters 10/90, 2" /- 0.2 mm; Center Thickness 8 mm; Thickness Tolerance ?0.4 mm; Surface Flatness (Peak to Valley) ?/10 @ 633 nm Over the Clear Aperture; Coating on	5.00	ks	4 111.00	20 555.00 Kč
		2.00	ks	4 683.00	9 366.00 Kč
64	BeamSplitters 30/70, 2" /- 0.2 mm; Center Thickness 8 mm; Thickness Tolerance ?0.4 mm; Surface Flatness (Peak to Valley) ?/10 @ 633 nm Over the Clear Aperture; Coating on	2.00	ks	4 111.00	8 222.00 Kč
65	BeamSplitters 90/10, 2" /- 0.2 mm; Center Thickness 8 mm; Thickness Tolerance ?0.4 mm; Surface Flatness (Peak to Valley) ?/10 @ 633 nm Over the Clear Aperture; Coating on	2.00	ks	4 683.00	9 366.00 Kč
66	BeamSplitters 70/30, 2" /- 0.2 mm; Center Thickness 8 mm; Thickness Tolerance ?0.4 mm; Surface Flatness (Peak to Valley) ?/10 @ 633 nm Over the Clear Aperture; Coating on	2.00	ks	4 111.00	8 222.00 Kč
67	Half waveplate Altechna 2-CPW-ZO-L2-0800 (mod.) AR coating range: 760-840 nm, Center wavelength 800 nm; Retardation: ?/2; Diameter=2"; Material: Single crystal quartz; Optical axis normal to facet on circumference of retarder; Wavefront distortion ?/10	1.00	ks	14 437.00	14 437.00 Kč
68	Quarter waveplate Altechna 2-CPW-ZO-L4-0800 (mod.) AR coating range: 760-840 nm, Center wavelength 800 nm; Retardation: ?/4; Diameter=2"; Material: Single crystal quartz; Optical axis normal to facet on circumference of retarder; Wavefront distortion ?	1.00	ks	17 152.00	17 152.00 Kč
69	Camera objective Nikon + Edmund Nikon 50/1,8 D AF + 54-341 Imaging lens f=50 mm, F/1.8 with adapter to C mount.	1.00	ks	6 933.00	6 933.00 Kč
70	Camera objective Tamron + Edmund TAMRON 70-300 mm f/4-5,6 SP Di VC USD pro Nikon + 54-341 Imaging lens f=70-300mm, F/4.0-5.6 with adapter to C mount.	1.00	ks	13 968.00	13 968.00 Kč
75	Mirror mounts 1" Thorlabs POLARIS-K1-2AH Optic Size: ?1"; Optic Thickness (Min): 0.08" (2 mm); Number of Adjusters: 2; Adjuster Drive: Low-Profile 5/64? Hex; Adjuster Pitch: TPI100; Actuator Matching Matched Actuator/Body Pairs; Resolution: 7 mrad/rev;	10.00	ks	3 186.00	31 860.00 Kč
76	Mirror mounts 2" Thorlabs POLARIS-K2S2 Optic Size: ?2"; Optic Thickness (Min): 0.14" (3.5 mm); Number of Adjusters: 2; Adjuster Drive: 5/64? Hex; Adjuster Pitch: TPI100; Actuator Matching Matched Actuator/Body Pairs; Resolution: 5 mrad/rev; Mechanical	3.00	ks	6 072.00	18 216.00 Kč
78	Mirror mounts 3" Thorlabs KS3 Optic Diameter: ?3?; Minimum Optic Thickness: 0.28?; Optical Axis Height: 2.13?; Angular Adjustment: +_4deg; Number of Adjusters: 2; Type of Adjusters: removable knobs; Adjuster Thread: ??-80; Resolution: 5.0 mrad/rev; Cle	10.00	ks	4 683.00	46 830.00 Kč
80	Waveplate holder Thorlabs RSP2D/M Optic diameter= 2". 360 degrees rotation. 1 deg sensitivity. (Must correspond with half wave and quarter wave plates size item 67 and 68).	3.00	ks	3 512.00	10 536.00 Kč
81	Iris Eksma Optics 992-1359-HT Iris Diaphragm, Continuously Variable; Minimum aperture 0 mm; Maximum aperture 100 mm ?2 mm, Leaves material: High temperature alloy up to 1000 deg.	4.00	ks	11 578.00	46 312.00 Kč
84	Laser Diode Modules Thorlabs CPS405 + AD11NT + LDS5-EC Wavelength 405 nm, Output Power >4 mW, Collimated, elliptical beam profile, including holder/adapter for 1" mirror mount and power supply.	1.00	ks	5 238.00	5 238.00 Kč
85	Laser Diode Modules Thorlabs CPS635R + AD11NT + LDS5-EC Wavelength 635 nm, Output Power >1 mW, Collimated, round beam profile, including holder/adapter for 1" mirror mount and power supply.	3.00	ks	2 781.00	8 343.00 Kč
87	IR diode 150 mW LASOS TLD-XT 830155 FS + 60FC-L-0-M125-54 Single mode fiber laser diode module @830 nm +-10nm, TEM 00, M2<1.2 + Large Fiber Collimator, - Diffraction Limited, Clean Gaussian beam, divergence, <0.05mrad, wavefront error <1/10 wave, Output	1.00	ks	43 764.00	43 764.00 Kč
88	XY translation mounts Newport LP-2A-XY Translating Lens Mount for ?2" Optics, Travel: ?0.04"; 1 Retaining Ring Included, Metric, High resolution adjusters with >=250 ?m/rev; Tip/Tilt Deviation: <100 ?rad.	2.00	ks	11 286.00	22 572.00 Kč
89	Optical Rails Thorlabs XT66-500 Rail: 500 mm Length, 66 mm Construction Rails have a dovetail mounting surface on all four sides for use in one-, two-, or three-dimensional constructions. Objects can be slid along the dovetail before being clamped int				

Žádáme Vás o zaslání daňových dokladů v elektronické podobě (skeny) na adresu efaktury@fzu.cz. O doručení dokladů obdržíte potvrzující e-mail. Objednávku nad 50 000 Kč uveřejníme v souladu se zákonem č. 340/2015 Sb., o zvláštních podmínkách účinnosti některých smluv, uveřejňování těchto smluv a o registru smluv, v platném znění.

Položka		Množství	MJ	Cena/MJ vč. DPH	Celkem s DPH
90	Optical Rails Thorlabs XT66-1000	1.00	ks	2 076.00	2 076.00 Kč
Rail: 1000 mm Length, 66 mm Construction Rails have a dovetail mounting surface on all four sides for use in one-, two-, or three-dimensional constructions. Objects can be slid along the dovetail before being clamped i					
91	Rails Carriage Thorlabs XT66P2/M	10.00	ks	1 695.00	16 950.00 Kč
Rail Carriage for 66 mm Rails with M4 & M6, Side-Locked Mounting Platform that Slides Along Rail, Must fit optical rails above.					
92	Pivot Platform Thorlabs XT66RC	10.00	ks	1 715.00	17 150.00 Kč
Rounded Dovetail Shape Allows Any Orientation Between Rail and Mounted Component; Contains One Counterbored Slot Compatible with 1/4"-20 (M6) Low-Profile Channel Screws and Low-Profile T-Nuts; Locking Screws Fasten with 2					
93	Blank Clamping Platform Thorlabs XT66C5	10.00	ks	694.00	6 940.00 Kč
Contains One 1/4" (M6) Counterbored Slot; Slides Along Rail Side Prior to Lockdown; Locking Screws Fasten with 2.5 mm Balldriver or Hex Key; Must fit optical rails above.					
96	Mounting Platforms Thorlabs XT66D2-50	5.00	ks	425.00	2 125.00 Kč
Mounting Platform, Three M6 Counterbores, 50 mm Long, Must fit optical rails above.					
97	Double Dovetail Clamps Thorlabs XT66C1	5.00	ks	438.00	2 190.00 Kč
Clamp Between Rails or Accessories, 20 mm Long Clamp, Must fit optical rails above.					
98	Double Dovetail Clamps Thorlabs XT66C2	5.00	ks	485.00	2 425.00 Kč
Clamp Between Rails or Accessories, 40 mm Long Clamp, Must fit optical rails above.					
99	Cross Clamp Thorlabs XT66CC	5.00	ks	1 314.00	6 570.00 Kč
Compact Clamp Joins Two 66 mm Rails at Right Angles; Single-Screw Clamping Mechanism; Must fit optical rails above.					
103	Clamping Platform Thorlabs XT66C4	5.00	ks	694.00	3 470.00 Kč
Contains One 1/4" (M6) Counterbored Slot; Slides Along Rail Side Prior to Lockdown; Locking Screws Fasten with 2.5 mm Balldriver or Hex Key, Must fit optical rails above.					
104	Clamps Thorlabs CL2/M-P5	5.00	ks	170.00	850.00 Kč
Heavy-Duty Variable Height Clamp, M6 Tapped, 76 mm +/- 0.5mm long, 15.5 mm +/-0.5 mm height.					
107	Clamps Thorlabs CL5-P5	5.00	ks	104.00	520.00 Kč
Table Clamp, L-Shape, 51 mm +/- 0.5mm long, 17 mm +/-0.5 mm height.					
108	Clamps Thorlabs BE1/M	30.00	ks	230.00	6 900.00 Kč
Studded Pedestal Base adapters, ?31.8 mm, M6 Thread.					
109	Clamps Thorlabs CF125-P5	15.00	ks	211.00	3 165.00 Kč
Short Clamping Fork, 31.5 mm (for 1/2" post holders) Counterbored Slot, M6, stainless steel.					
113	glass lens 2" f=60mm Thorlabs LA1401	5.00	ks	885.00	4 425.00 Kč
lens ?2 inch, plano-convex, focal length ~60 mm, uncoated, Surface Irregularity (Peak to Valley) ?/4, Wavelength Range 350 nm - 2.0 ?m.					
114	glass lens 2" f=100mm Thorlabs LA1050	5.00	ks	722.00	3 610.00 Kč
lens ?2 inch, plano-convex, focal length ~100 mm, uncoated, Surface Irregularity (Peak to Valley) ?/4, Wavelength Range 350 nm - 2.0 ?m.					
115	glass lens 2" f=150mm Thorlabs LA1417	5.00	ks	708.00	3 540.00 Kč
lens ?2 inch, plano-convex, focal length ~150 mm, uncoated, Surface Irregularity (Peak to Valley) ?/4, Wavelength Range 350 nm - 2.0 ?m.					
116	glass lens 2" f=200mm Thorlabs LA1979	5.00	ks	708.00	3 540.00 Kč
lens ?2 inch, plano-convex, focal length ~200 mm, uncoated, Surface Irregularity (Peak to Valley) ?/4, Wavelength Range 350 nm - 2.0 ?m.					
117	glass lens 2" f=250mm Thorlabs LA1301	5.00	ks	1 116.00	5 580.00 Kč
lens ?2 inch, plano-convex, focal length ~250 mm, uncoated, Surface Irregularity (Peak to Valley) ?/4, Wavelength Range 350 nm - 2.0 ?m.					
118	glass lens 2" f=500mm Thorlabs LA1380	5.00	ks	756.00	3 780.00 Kč
lens ?2 inch, plano-convex, focal length ~500 mm, uncoated, Surface Irregularity (Peak to Valley) ?/4, Wavelength Range 350 nm - 2.0 ?m.					
119	glass lens 2" f=1000mm Thorlabs LA1779	5.00	ks	1 062.00	5 310.00 Kč
lens ?2 inch, plano-convex, focal length ~1000 mm, uncoated, Surface Irregularity (Peak to Valley) ?/4, Wavelength Range 350 nm - 2.0 ?m.					
120	glass lens 1" f=50mm Thorlabs LA1131	2.00	ks	529.00	1 058.00 Kč
lens ?2 inch, plano-convex, focal length ~50 mm, uncoated, Surface Irregularity (Peak to Valley) ?/4, Wavelength Range 350 nm - 2.0 ?m.					

Zádáme Vás o zaslání daňových dokladů v elektronické podobě (skeny) na adresu efaktury@fzu.cz. O doručení dokladů obdržíte potvrzující e-mail. Objednávku nad 50 000 Kč uveřejníme v souladu se zákonem č. 340/2015 Sb., o zvláštních podmínkách účinnosti některých smluv, uveřejňování těchto smluv a o registru smluv, v platném znění.

Položka		Množství	MJ	Cena/MJ vč. DPH	Celkem s DPH	
121	glass lens 1" f=100mm Irregularity (Peak to Valley) 1/4, Wavelength Range 350 nm - 2.0 μm.	Thorlabs LA1509	lens 1 inch, plano-convex, focal length ~100 mm, uncoated, Surface	3.00 ks	502.00	1 506.00 Kč
131	polarizer 1" ,500-700nm >1000:1 at 500-700 nm, Reflectance over Coating Range (Avg.) < 0.5% at 0° AOI.	Thorlabs LPVISE100-A	1" film polarizer, extinction ratio > 100:1 at 400-700 nm,	5.00 ks	2 253.00	11 265.00 Kč
132	variable circular continuous ND filter 50 mm max OD 2 Continuously Variable, Reflective Neutral Density Filter for attenuation via rotation, diameter 50mm, Optical density range 0-4, Optical Density Tolerance ±5% (Thorlabs NDC-50C-4 + NDC-PM	Circular,	1.00 ks	9 652.00	9 652.00 Kč
133	beam splitter 2" 50:50 thickness 8 mm, Damage Threshold > 10 J/cm ² (810 nm, 10 ns, 10 Hz, 70.130 mm), Splitter Ratio Tolerance ±12% Over Entire Wavelength R	Thorlabs BSW27	beam splitter 2 inch, split ratio 50:50, fused silica, coating 350 - 1100 nm,	5.00 ks	7 950.00	39 750.00 Kč
134	Aluminum Breadboard, 100 mm x 300 mm 12.7 mm, M6 Taps.	Newport M-SA2-04X12	Aluminum Breadboard, 100 mm x 300 mm x	3.00 ks	1 393.00	4 179.00 Kč
135	Aluminum Breadboard, 300 mm x 300 mm M6 Taps.	Newport M-SA2-11	Aluminum Breadboard, 300 mm x 300 mm x 12.7 mm,	3.00 ks	3 192.00	9 576.00 Kč
136	Position-Maintaining Post Collar Maintain the established height and rotational orientation of a 1/2" Post and Post Holder, ±0.5° Angular Repeatability.	Thorlabs RMC	Position-Maintaining Post Collar for 1/2" Posts and Post Holders,	50.00 ks	632.00	31 600.00 Kč
139	90° Angle Clamp, TOP clamp for mounting two posts together perpendicularly in one plane).	Thorlabs RA180/M	90° Angle Clamp for 1/2" Posts, 5 mm Hex, M6 Stud (lockable	20.00 ks	260.00	5 200.00 Kč
140	90° Angle Clamp, 25 mm (lockable clamp for mounting two posts 1/2" and 25 mm together perpendicularly).	Thorlabs RA90RS/M	90° Angle Clamp for 1/2" and 25 mm Posts, 5 mm Hex	10.00 ks	645.00	6 450.00 Kč
144	5 mm Hex-Locking Thumbscrew 1.0 Thread.	Thorlabs TS6H/M	Spring-Loaded 5 mm Hex-Locking Thumbscrew, M6 x	20.00 ks	304.00	6 080.00 Kč
145	M4 to M6 Adapter Threads.	Thorlabs AE4M6M	Dual Threaded Adapter with Internal M4 x 0.7 Threads and External M6 x 1.0	50.00 ks	104.00	5 200.00 Kč
155	25 mm Post Spacer, L=5 mm Clearance Hole.	Thorlabs RS5/M	25 mm Post Spacer for 25 mm pillars, Thickness = 5 mm, M6	10.00 ks	233.00	2 330.00 Kč
156	25 mm Post Spacer, L=10 mm Clearance Hole.	Thorlabs RS10/M	25 mm Post Spacer for 25 mm pillars, Thickness = 10 mm, M6	10.00 ks	286.00	2 860.00 Kč
157	Post Mounting Clamp for 25 mm Post mm Mounting Plate, M6 Tapped Holes (Qty. 24), M4 Tapped Holes (Qty. 25).	Thorlabs C1001/M	Post Mounting Clamp for 25 mm Post, 50.8 mm x 50.8	5.00 ks	1 899.00	9 495.00 Kč
159	1.5" Mounting Post L=25mm Stainless Steel, tapped on both ends with a M6 tapped hole.	Thorlabs P25/M	1.5" Mounting Post, M6 Taps, L = 25 mm, Solid Nonmagnetic	5.00 ks	493.00	2 465.00 Kč
160	1.5" Mounting Post L=30mm Stainless Steel, tapped on both ends with a M6 tapped hole.	Thorlabs P30/M	1.5" Mounting Post, M6 Taps, L = 30 mm, Solid Nonmagnetic	5.00 ks	555.00	2 775.00 Kč
161	1.5" Mounting Post L=50mm Stainless Steel, tapped on both ends with a M6 tapped hole.	Thorlabs P50/M	1.5" Mounting Post, M6 Taps, L = 50 mm, Solid Nonmagnetic	5.00 ks	659.00	3 295.00 Kč
162	1.5" Mounting Post L=75mm Stainless Steel, tapped on both ends with a M6 tapped hole.	Thorlabs P75M	1.5" Mounting Post, M6 Taps, L = 75 mm, Solid Nonmagnetic	5.00 ks	837.00	4 185.00 Kč
163	1.5" Mounting Post L=100mm Stainless Steel, tapped on both ends with a M6 tapped hole.	Thorlabs P100/M	1.5" Mounting Post, M6 Taps, L = 100 mm, Solid Nonmagnetic	5.00 ks	960.00	4 800.00 Kč
164	1.5" Mounting Post L=125mm Stainless Steel, tapped on both ends with a M6 tapped hole.	Thorlabs P125/M	1.5" Mounting Post, M6 Taps, L = 125 mm, Solid Nonmagnetic	5.00 ks	1 116.00	5 580.00 Kč
165	1.5" Mounting Post L=150mm Stainless Steel, tapped on both ends with a M6 tapped hole.	Thorlabs P150/M	1.5" Mounting Post, M6 Taps, L = 150 mm, Solid Nonmagnetic	5.00 ks	1 239.00	6 195.00 Kč

Zádáme Vás o zaslání daňových dokladů v elektronické podobě (skeny) na adresu efakury@fzu.cz. O doručení dokladů obdržíte potvrzující e-mail. Objednávku nad 50 000 Kč uveřejníme v souladu se zákonem č. 340/2015 Sb., o zvláštních podmínkách účinnosti některých smluv, uveřejňování těchto smluv a o registru smluv, v platném znění.

Položka		Množství	MJ	Cena/MJ vč. DPH	Celkem s DPH
166	?1.5" Mounting Post L=200mm Thorlabs P200/M Stainless Steel, tapped on both ends with a M6 tapped hole.	5.00	ks	1 368.00	6 840.00 Kč
167	?1.5" Mounting Post L=250mm Thorlabs P250/M Stainless Steel, tapped on both ends with a M6 tapped hole.	5.00	ks	1 722.00	8 610.00 Kč
168	?1.5" Mounting Post L=300mm Thorlabs P300/M Stainless Steel, tapped on both ends with a M6 tapped hole.	5.00	ks	1 994.00	9 970.00 Kč
172	?1.5" Post Pedestal Base Adapter Thorlabs PB4/M 1.5" Mounting Posts	10.00	ks	313.00	3 130.00 Kč
173	Clamping Fork for ?1.5" Pedestal Post Thorlabs PF175 Base Adapter, Universal, For mounting ?1.5" Post Pedestal Base Adapter to an optical table.	10.00	ks	441.00	4 410.00 Kč
174	?1.5" Post Base Thorlabs PB2/M Thick, Four counterbored slots.	10.00	ks	678.00	6 780.00 Kč
177	Kinematic Base 50 mm x 50 mm Thorlabs KB50/M Top and Bottom Plate, 30 ?rad Angular Repeatability, 30 ?m Lateral Repeatability, M6 Mounting, M6 and M4 Tapped Holes.	2.00	ks	2 022.00	4 044.00 Kč
178	Kinematic Base 75 mm x 75 mm Thorlabs KB75/M Top and Bottom Plate, 30 ?rad Angular Repeatability, 82 ?m Lateral Repeatability, M6 Mounting, M6 and M4 Tapped Holes.	2.00	ks	2 287.00	4 574.00 Kč
180	Right-Angle Bracket Thorlabs AB90A/M Each Side.	5.00	ks	651.00	3 255.00 Kč
181	Slim Right-Angle Bracket Thorlabs AB90B/M Holes.	5.00	ks	651.00	3 255.00 Kč
183	Right-Angle Bracket, Medium Thorlabs AP90/M slots, M6 tapped holes, Parallel and Perpendicular to Within 0.05 mm.	2.00	ks	1 974.00	3 948.00 Kč
187	Iris 0.8-25mm zero aperture Thorlabs ID25Z/M Black Spring Steel Leaves, mounted on a ?12.7 mm post, metric.	20.00	ks	1 736.00	34 720.00 Kč
188	Iris 0.8-25mm Thorlabs ID25/M mounted on a ?12.7 mm post, metric.	20.00	ks	1 395.00	27 900.00 Kč
189	Iris 2-50mm Thorlabs ID50/M mounted on a ?12.7 mm post, metric.	20.00	ks	2 968.00	59 360.00 Kč
190	12.7 mm XYZ Translation Stage Newport M-460A-XYZ + 3x SM-13 Micrometers, M6 Taps, Resolution: 500 ?m Translation per Revolution.	1.00	ks	20 543.00	20 543.00 Kč
194	High-Precision Rotation Mount Newport M-481-A per Division, M6 and M4 Taps, SM1-Threaded Center Hole Accepts ?1" (?25.4 mm) Optics up to 17 mm Thick.	5.00	ks	7 486.00	37 430.00 Kč
198	Kinematic Mirror Mount for ?1" Optics Newport M1 4?, Resolution: 8 mrad (0.5?) per rev via, Two Counterbored M4 Through Holes Allow for Left- or Right-Handed Orientation.	10.00	ks	731.00	7 310.00 Kč
199	Kinematic Mirror Mount for ?2" Optics Thorlabs KS2 3?, Resolution: 5 mrad (0.3?) per rev via, Six Counterbored M4 Through Holes Allow for Left- or Right-Handed Orientation.	15.00	ks	3 240.00	48 600.00 Kč
201	Fixed ?25 mm Optical Mount, Metric Newport M-LH-1A Tapped Hole, Minimum Optic Thickness 3.73 mm.	20.00	ks	345.00	6 900.00 Kč
202	Fixed ?50.8 mm Optical Mount, Metric Newport M-LH-2A Tapped Hole, Minimum Optic Thickness 5.76 mm.	20.00	ks	609.00	12 180.00 Kč
203	Kinematic Mirror Mount for ?1" Optics, clear edge Newport M1Q Angular Range: ?3?, Resolution: 5 mrad (0.5?) per rev via, one edge of held mirror is let free.	10.00	ks	812.00	8 120.00 Kč
204	Kinematic Mirror Mount for ?2" Optics, clear edge Newport U200-A2K Optics, Angular Range: ?3?, Resolution: 5 mrad (0.5?) per rev via, one edge of held mirror is let free.				

Položka	Množství	MJ	Cena/MJ vč. DPH	Celkem s DPH
	10.00	ks	4 004.00	40 040.00 Kč
206 flip mount for ?1" Optics and filters Thorlabs TRF90/M Mount for ?1" Filters and Optics, threaded inside (SM1), allow optics to be easily inserted or removed from the beampath by flipping. Detent mechanism with holding force at the 0° and 90° position	5.00	ks	2 028.00	10 140.00 Kč
214 Al Half Inch posts 20mm Thorlabs TRA20/M ?12.7 mm Optical Post, M4 Setscrew, M6 Tap, L = 20 mm, Bottom-Located M6 Tapped Hole and Top-Located M4 Removable Setscrew, Aluminum.	20.00	ks	162.00	3 240.00 Kč
215 Al alf Inch posts 30mm Thorlabs TRA30/M ?12.7 mm Optical Post, M4 Setscrew, M6 Tap, L = 30 mm, Bottom-Located M6 Tapped Hole and Top-Located M4 Removable Setscrew, Aluminum.	20.00	ks	162.00	3 240.00 Kč
216 Al Half Inch posts 40mm Thorlabs TRA40/M ?12.7 mm Optical Post, M4 Setscrew, M6 Tap, L = 40 mm, Bottom-Located M6 Tapped Hole and Top-Located M4 Removable Setscrew, Aluminum.	20.00	ks	170.00	3 400.00 Kč
217 Al Half Inch posts 50mm Thorlabs TRA50/M ?12.7 mm Optical Post, M4 Setscrew, M6 Tap, L = 50 mm, Bottom-Located M6 Tapped Hole and Top-Located M4 Removable Setscrew, Aluminum.	40.00	ks	174.00	6 960.00 Kč
218 Al Half Inch posts 75mm Thorlabs TRA75/M ?12.7 mm Optical Post, M4 Setscrew, M6 Tap, L = 75 mm, Bottom-Located M6 Tapped Hole and Top-Located M4 Removable Setscrew, Aluminum.	40.00	ks	182.00	7 280.00 Kč
219 Al Half Inch posts 100mm Thorlabs TRA100/M ?12.7 mm Optical Post, M4 Setscrew, M6 Tap, L = 100 mm, Bottom-Located M6 Tapped Hole and Top-Located M4 Removable Setscrew, Aluminum.	40.00	ks	195.00	7 800.00 Kč
220 Al Half Inch posts 150mm Thorlabs TRA150/M ?12.7 mm Optical Post, M4 Setscrew, M6 Tap, L = 150 mm, Bottom-Located M6 Tapped Hole and Top-Located M4 Removable Setscrew, Aluminum.	20.00	ks	221.00	4 420.00 Kč
223 Optical Rails, 66mm Thorlabs XT66SP-500 Rail: 500 mm Length, 66 mm Construction Rails have a dovetail mounting surface for One-Dimensional Constructions; Objects can be slid along the dovetail before being clamped into place. Clear anodized coating.	2.00	ks	776.00	1 552.00 Kč
224 Optical Rails, 66mm, 1m Thorlabs XT66P-1000 Rail: 1000 mm Length, 66 mm Construction Rails have a dovetail mounting surface for One-Dimensional Constructions; Objects can be slid along the dovetail before being clamped into place. Clear anodized coat	1.00	ks	1 538.00	1 538.00 Kč
233 Half Inch post 20mm, vacuum Thorlabs TR20V/M ?12.7 mm Optical Post, Stainless steel, M4 Setscrew, M6 Tap, L = 20 mm, Vacuum compatibility: 1.3*1E-6 mbar.	20.00	ks	246.00	4 920.00 Kč
234 Half Inch post 30mm, vacuum Thorlabs TR30V/M ?12.7 mm Optical Post, Stainless steel, M4 Setscrew, M6 Tap, L = 30 mm, Vacuum compatibility: 1.3*1E-6 mbar.	20.00	ks	260.00	5 200.00 Kč
235 Half Inch post 40mm, vacuum Thorlabs TR40V/M ?12.7 mm Optical Post, Stainless steel, M4 Setscrew, M6 Tap, L = 40 mm, Vacuum compatibility: 1.3*1E-6 mbar.	20.00	ks	308.00	6 160.00 Kč
236 Half Inch post 50mm, vacuum Thorlabs TR50V/M ?12.7 mm Optical Post, Stainless steel, M4 Setscrew, M6 Tap, L = 50 mm, Vacuum compatibility: 1.3*1E-6 mbar.	30.00	ks	316.00	9 480.00 Kč
237 Half Inch post 75mm, vacuum Thorlabs TR75V/M ?12.7 mm Optical Post, Stainless steel, M4 Setscrew, M6 Tap, L = 75 mm, Vacuum compatibility: 1.3*1E-6 mbar.	30.00	ks	327.00	9 810.00 Kč
238 post holder 20mm, vacuum Thorlabs PH20V/M Post Holder with Hex Locking Thumbscrew, L= 20 mm, wide relief cut that provides two lines of contact for highly stable post mountin Vacuum compatibility: 1.3*1E-6 mbar.	20.00	ks	742.00	14 840.00 Kč
239 post holder 30mm, vacuum Thorlabs PH30V/M Post Holder with Hex Locking Thumbscrew, L= 30 mm, wide relief cut that provides two lines of contact for highly stable post mountin Vacuum compatibility: 1.3*1E-6 mbar.	20.00	ks	749.00	14 980.00 Kč
240 post holder 40mm, vacuum Thorlabs PH40V/M Post Holder with Hex Locking Thumbscrew, L= 40 mm, wide relief cut that provides two lines of contact for highly stable post mounting, Vacuum compatibility: 1.3*1E-6 mbar.	20.00	ks	776.00	15 520.00 Kč
241 post holder 50mm, vacuum Thorlabs PH50V/M Post Holder with Hex Locking Thumbscrew, L= 50 mm, wide relief cut that provides two lines of contact for highly stable post mounting, Vacuum compatibility: 1.3*1E-6 mbar.	20.00	ks	790.00	15 800.00 Kč
242 post holder 75mm, vacuum Thorlabs PH75V/M Post Holder with Hex Locking Thumbscrew, L= 75 mm, wide relief cut that provides two lines of contact for highly stable post mounting, Vacuum compatibility: 1.3*1E-6 mbar.	20.00	ks	858.00	17 160.00 Kč

Položka	Množství	MJ	Cena/MJ vč. DPH	Celkem s DPH
243 mounting base 1, vacuum 1.3*1E-6 mbar.	Thorlabs BA1V/M	Mounting Base, 25 mm x 75 mm x 10 mm, Vacuum compatibility:		
	30.00	ks	310.00	9 300.00 Kč
244 mounting base 2, vacuum 1.3*1E-6 mbar.	Thorlabs BA1SV/M	Mounting Base, 25 mm x 58 mm x 10 mm, Vacuum compatibility:		
	30.00	ks	310.00	9 300.00 Kč
245 mounting base 3, vacuum 1.3*1E-6 mbar.	Thorlabs BA2V/M	Mounting Base, 50 mm x 75 mm x 10 mm, Vacuum compatibility:		
	30.00	ks	436.00	13 080.00 Kč
246 vacuum thumbscrews Thorlabs *1E-6 mbar.	TS6HV/M	5 mm Hex-Locking Thumbscrew, M6 x 1.0 Thread, Vacuum compatibility: 1.3		
	10.00	ks	133.00	1 330.00 Kč
249 Kinematic ?2" Mirror Mount inserted from the rear side, Three-Point Contact Plate Secures Optic, Hardened Stainless Steel Ball Contacts with Sapphire Seats for Durability, parts	Thorlabs POLARIS-K2F1	Kinematic Mirror Mounts for 2? optics, the optic is		
	20.00	ks	7 106.00	142 120.00 Kč
Dorovnanie	1.00	ks	20.00	20.00 Kč
DPH	1.00	ks	401 657.76	401 657.76 Kč

Celkem:**2 314 313.76 Kč***Konec přílohy k objednávce č.: 0018920233*