

Adresa:

UNIVERZITA KARLOVA
MATEMATICKO FYZIKALNI FAKULTA

V HOLESOVICKACH 2
CZ 180 00 PRAHA

Nabídka 11 18000721 - 2018-04-27

Zákaznické číslo: 101362
DIČ: CZ00216208

Datum poptávky: 2018-04-27

Zpracovává:	Mirka Frysova
Přímá linka:	+420 257 923 888
E-Mail:	Mirka.Frysova@pfeiffer-vacuum.cz
Náš kontakt:	Jiri Drbohlav
Platná do:	2018-06-30
Dodací lhůta:	5 měsíců

Vážení

děkujeme Vám za Váš zájem o vakuové komponenty a technologie firmy PFEIFFER Vacuum a zasíláme Vám naši nabídku:
Pro nabídku a dodávku platí Všeobecné obchodní podmínky firmy Pfeiffer Vacuum.

Pol.	Produkt	Množství	Cena v EUR
1.0	PM 193 301 -T Sales Promotion Turbo HiPace 80 Package DN 63 CF-F with DCU consisting of - HiPace 80, DN 63 CF, with TC 110 (PM P03 941) - DCU 110 (PM C01 820) - Cable TC 110 - TPS/DCU 110/180, 3 m (PM 061 351 -T) - Air cooling, 24 V DC, for TC 110 (PM Z01 300 AT)	1 ks	
2.0	P 4564 309 ZA Mains cable, 230V AC, (DE) length: 3m with Schuko-plug CEE (7) VII Euro style EN 60320/C13	1 ks	
3.0	PM 016 312 Splinter shield for DN 63 CF-F	1 ks	
4.0	PK T05 065 A MVP 015-4 Membranvakuumpumpe 230 V, 50 Hz Robust, compact and high-performance diaphragm pump - Pumping speed at 50 Hz: 0.5 m ³ /h - Ultimate pressure without gas ballast: 5 · 10 ⁻¹ hPa Absolutely oil-free Very quiet and low vibration Applicable as a backing pump for turbo pumps and as stand-alone version - Flange (in): DN 16 ISO-KF; G 1/8" - Flange (out): G 1/8" + silencer - Mains requirement: voltage 50 Hz: 230 V - Cooling method, standard: Air - Emission sound pressure level without gas ballast: = 52 dB(A)	1 ks	



12

Nabídka 11 18000721 - 27.04.2018

Pol.	Produkt	Množství	Cena v EUR
5.0	120SWN016-1000 Corrugated Hose, DN 16 ISO-KF Stainless steel, flexible, length 1000 mm	1 ks	
6.0	122ZRG016 Centering Ring, DN 16 ISO-KF Stainless Steel 304/1.4301, O-Ring FKM	2 ks	
7.0	110BSR016 Klema, DN 10 / 16 ISO-KF Aluminum ADC 12, pro elastomerová těsnění	2 ks	
8.0	PT T02 350 010 PKR 360, Active Pirani/ Cold cathode gauge DN 40 CF-F low current Compact combination sensor – insensitive to gas inrush - cold cathode gauge according to the inverted magnetron principle - Display range: 1 · 10 ⁻⁹ – 1000 hPa - Measurement range: 1 · 10 ⁻⁸ – 1000 hPa - Accuracy: ± 30 % of reading (10 ⁻⁸ – 100 hPa) - Accuracy: ± 50 % of reading (100 – 1000 hPa) - Supply voltage: 14.5 – 30 V DC - Analog output signal: 0 – 10.5 V, logarithmic - minimum magnetic stray field - optimized for applications in the medium vacuum range	1 ks	
9.0	PT 448 250 -T Sensor cable CG for Single/Dual/MaxiGauge length: 3 m	1 ks	
10.0	PT G28 290 TPG 362, DualGauge Display and control unit for two gauges 100-250 V AC, 50/60 Hz - For operation of two gauges with analog output signal - Brilliant display - Simultaneous display of both pressure readings - Simple to operate - Four freely configurable relay set points - Versatile connectivity - USB - RS-485 - Ethernet - Direct data storage on USB flash memory (data and settings) - Can be used as table top or as rack mount unit	1 ks	
11.0	P 4564 309 YU Mains cable, 230V AC, (DE) 1 mm ² , length: 2,5 m with Schuko-plug CEE (7) VII Euro style EN 60320/C13	1 ks	

Celková nabízená cena v CZK bez DPH: 174.700,-



13

Nabídka 11 18000721 - 27.04.2018

Pol.	Produkt	Množství	Cena v EUR
------	---------	----------	------------

Daňový základ	6.517,80
DPH 0,0%	0,00
Celkem k platbě	6.517,80

Pfeiffer Vacuum Austria GmbH

Dodací podmínky: FCA

Doprava: UPS - United Parcel Service

Váha - Netto: 17,908

Platba: 30 dní po vystavení, netto

Bankovní spojení:

Swift/BIC:

Kód banky:

Číslo účtu:

IBAN:

UniCredit Bank Austria AG

BKAUATWW

11000

09604401100

AT971100009604401100

Erste Bank der Sparkassen AG

GIBAATWW

20111

28319928000

AT922011128319928000

- Anzeige / Advert -

VACUUM SOLUTIONS FROM A SINGLE SOURCE
www.pfeiffer-vacuum.com

LB

14