

Adresa:

USTAV FYZIKALNI CHEMIE
 J. HEYROVSKEHO AVCR, v.v.i.
 NAKUPNI ODDELENI
 [REDACTED]

DOLEJSKOVA 3
 CZ 182 23 PRAHA

Nabídka 11 18001940 - 2018-10-16

Zákaznické číslo: 102151
DIČ: CZ61388955
Datum poptávky: 2018-10-11

Zpracovává:	[REDACTED]
Přímá linka:	[REDACTED]
E-Mail:	[REDACTED]
Náš kontakt:	[REDACTED]
Platná do:	2018-10-31
Dodací lhůta:	8 týdnů

Vážení

děkujeme Vám za Váš zájem o vakuové komponenty a technologie firmy PFEIFFER Vacuum a zasíláme Vám naši nabídku:
 Pro nabídku a dodávku platí Všeobecné obchodní podmínky firmy Pfeiffer Vacuum.

Pol.	Produkt	Množství	Cena v EUR	
			za MJ	Celkem
1.0	PK 195 281 -T DUO 3, Rotary vane pump 115/230 V, 50/60 Hz with ONFR 1-9, lubrication P3 Sales Promotion DuoLine Consisting of: -Duo 3, 1-phase motor, 115/230 V (±10 %), 50/60 Hz Dual-stage, high-performance rotary vane pump with a pumping speed of 2.5 m³/h at 50 Hz / 2.9 m³/h at 60 Hz With single-phase motor, IEC-C14-connector in terminal box With bi-metal-switch for optimum motor protection Integrated gas ballast and safety valve Pump and motor certified according to UL and IEC 61010 For all low and medium vacuum applications First filling of operating fluid included in delivery -OME16 S oil mist eliminator -Clamping ring DN 10-16 ISO-KF -Seal DN 16 ISO-KF -Oil return unit from OME 16 S to Duo 3	1 ks	[REDACTED]	[REDACTED]
2.0	PK 050 109 Mains cable for MVP 035-2 to MVP 100-3C and DUO 1.3 - 20 with Schuko-plug with right angle coupler plug	1 ks	[REDACTED]	[REDACTED]

Nabídka 11 18001940 - 16.10.2018

Pol.	Produkt	Množství	Cena v EUR	
			za MJ	Celkem
3.0	PK 195 481 -T DUO 6, Rotary vane pump 115/230 V, 50/60 Hz with ONFR 1-9, lubrication P3 Sales Promotion DuoLine Consisting of: -Duo 6, 1-phase motor, 115/230 V (±10 %), 50/60 Hz Dual-stage, high-performance rotary vane pump with a pumping speed of 5 m³/h at 50 Hz / 6 m³/h at 60 Hz With single-phase motor, IEC-C14-connector in terminal box With bi-metal-switch for optimum motor protection Integrated gas ballast and safety valve Pump and motor certified according to UL and IEC 61010 For all low and medium vacuum applications First filling of operating fluid included in delivery -OME16 S oil mist eliminator -Clamping ring DN 10-16 ISO-KF -Seal DN 16 ISO-KF -Oil return unit from OME 16 S to Duo 6	2 ks		
4.0	PK 050 109 Mains cable for MVP 035-2 to MVP 100-3C and DUO 1.3 - 20 with Schuko-plug with right angle coupler plug	2 ks		
5.0	PK 195 881 -T DUO 11, Rotary vane pump 115/230 V, 50/60 Hz with ONFR 16 S, lubrication P3 Sales Promotion DuoLine Consisting of: -Duo 11, 1-phase motor, 115/230 V (±10 %), 50/60 Hz Dual-stage, high-performance rotary vane pump with a pumping speed of 9 m³/h at 50 Hz / 10.5 m³/h at 60 Hz With single-phase motor, IEC-C14-connector in terminal box With bi-metal-switch for optimum motor protection Integrated gas ballast and safety valve Pump and motor certified according to UL and IEC 61010 For all low and medium vacuum applications First filling of operating fluid included in delivery -OME16 S oil mist eliminator -Clamping ring DN 10-16 ISO-KF -Seal DN 16 ISO-KF -Oil return unit from OME 16 S to Duo 11	1 ks		
6.0	PK 050 109 Mains cable for MVP 035-2 to MVP 100-3C and DUO 1.3 - 20 with Schuko-plug with right angle coupler plug	1 ks		
7.0	PT T00 140 010 IKR 360, Active Cold cathode gauge DN 25 ISO- KF low current Compact cold cathode ionization gauge according to the inverted magnetron principle - Display range: 1 · 10 ⁻⁹ – 10 ⁻² hPa - Measurement range: 1 · 10 ⁻⁸ – 10 ⁻² hPa - Accuracy: ± 30 % of reading - Supply voltage: 14.5 – 30 V DC - Analog output signal: 0 – 10.5 V, logarithmic - Floating two-way contact: 30 V DC, 1 A - minimum magnetic stray field - optimized for applications in the medium vacuum range	1 ks		

Nabídka 11 18001940 - 16.10.2018

Pol.	Produkt	Množství	Cena v EUR	
			za MJ	Celkem
8.0	PT T01 140 010 IKR 361, Active Cold cathode gauge DN 25 ISO-KF high current Compact cold cathode ionization gauge according to the inverted magnetron principle - Display range: 1 · 10 ⁻⁹ – 10 ⁻² hPa - Measurement range: 1 · 10 ⁻⁸ – 10 ⁻² hPa - Accuracy: ± 30 % of reading - Supply voltage: 14.5 – 30 V DC - Analog output signal: 0 – 10.5 V, logarithmic - Floating two-way contact: 30 V DC, 1 A - minimum magnetic stray field - optimized for high vacuum applications	1 ks	■	■
9.0	PT R26 770 B TPR 270 Active Pirani Gauge DN 16 ISO-KF compact and rugged Pirani sensor measurement range: 1 · 10 ⁻⁴ – 1000 hPa accuracy: ± 30% des Messwertes (20 – 1000 hPa) accuracy: ± 10% des Messwertes (2 · 10 ⁻³ – 20 hPa) accuracy: < 2 · 10 ⁻³ hPa; factor 2 output signal: 1,5 - 8,5 V, logarithmic backout temperature: 80°C at flange voltage supply: 15 - 30 V DC	4 ks	■	■
10.0	PT 448 250 -T Sensor cable CG for Single/Dual/MaxiGauge length: 3 m	6 ks	■	■
11.0	PT 448 251 -T Sensor cable CG for Single/Dual/MaxiGauge length: 6 m	2 ks	■	■
12.0	PT G28 770 TPG 366, MaxiGauge Display and control unit for six gauges 100-240 V AC, 50/60 Hz - For operation of six gauges with analog output signal - Brilliant display - Simultaneous display of all six pressure readings - Simple to operate - Six freely configurable relay set points - Versatile connectivity - USB - RS-485 - Ethernet - Direct data storage on USB flash memory (data and settings) - Can be used as table top or as rack mount unit	1 ks	■	■
13.0	P 4564 309 YU Mains cable, 230V AC, (DE) 1 mm ² , length: 2,5 m with Schuko-plug CEE (7) VII Euro style EN 60320/C13	1 ks	■	■
14.0	420XSS016-10 Multi-pin, DN 16 CF Alumel-conductor, 10 pins, 700 V DC, 10 A, w/ plug	1 ks	■	■
15.0	420XFL016-PP Fluid Feedthrough, Single Tube, DN 16 CF Stainless steel, tube end both sides	1 ks	■	■
16.0	XKL015A Contact Clamp BeCu (gold-plated), 1 piece per package	15 ks	■	■

Nabídka 11 18001940 - 16.10.2018

Pol.	Produkt	Množství	Cena v EUR	
			za MJ	Celkem
17.0	120SWN025-2000 Corrugated Hose, DN 25 ISO-KF Stainless steel, flexible, length 2000 mm	1 ks	████	████
18.0	120SWN025-1000 Corrugated Hose, DN 25 ISO-KF Stainless steel, flexible, length 1000 mm	4 ks	████	████
19.0	120SWN025-0500 Corrugated Hose, DN 25 KF Stainless steel, flexible, length 500 mm	2 ks	████	████
20.0	120SWN016-1000 Corrugated Hose, DN 16 ISO-KF Stainless steel, flexible, length 1000 mm	4 ks	████	████
21.0	120SWN016-0500 Corrugated Hose, DN 16 ISO-KF Stainless steel, flexible, length 500 mm	2 ks	████	████
22.0	110RKS025 4-Way Cross, DN 25 ISO-KF Aluminum EN AW- 6082/3.2315	5 ks	████	████
23.0	110RKS016 4-Way Cross, DN 16 ISO-KF Aluminum EN AW- 6082/3.2315	5 ks	████	████
24.0	110RTS025 Tee, DN 25 ISO-KF Aluminum EN AW- 6082/3.2315, length 100 mm	5 ks	████	████
25.0	110RTS016 Tee, DN 16 ISO-KF Aluminum EN AW- 6082/3.2315, length 80 mm	5 ks	████	████
26.0	120RRK040-025-40 Conical Reducer, DN 40 ISO-KF DN 40-25 ISO- KF, stainless Steel, length 40 mm	1 ks	████	████
27.0	110RRG025-016-40 Straight Reducer, DN 25 ISO-KF DN 25-16 ISO- KF, aluminum, length 40 mm	10 ks	████	████
28.0	110BSR016 Klema, DN 10 / 16 ISO-KF Aluminum ADC 12, pro elastomerová těsnění	10 ks	████	████
29.0	110BSR025 Klema, DN 20 / 25 ISO-KF Aluminum ADC 12, pro elastomerová těsnění	10 ks	████	████
30.0	PF 630 010 -T ULD 016 S, DN 16 CF-R Linear feedthrough, bellows-sealed, manual	1 ks	████	████
31.0	420BST-M6x25 Stud Screw Set, DN 25-40 CF Stainless Steel A2-70, 10 count M6	3 ks	████	████
32.0	420BST-M6x35 Stud Screw Set, DN 25-40 CF Stainless Steel A2-70, 10 count M6	3 ks	████	████
33.0	420BMD100 Plate Nut Set, DN 100 CF Stainless steel 304, screws: A2-70 8 count M8	1 ks	████	████

Nabídka 11 18001940 - 16.10.2018

Pol.	Produkt	Množství	Cena v EUR	
			za MJ	Celkem

Ceny se rozumí "ex works", bez obalu a dopravného, bez DPH.

Cena obalu, dopravného a pojistného činí **270,00 EUR**.

Pro nabídku a dodávku platí všeobecné dodací podmínky firmy PFEIFFER

Vacuum GmbH dostupné na www.pfeiffer-vacuum.net.

Instalace technikem dodavatele není součástí nabídky ani podmínkou záruky.

Instalace musí být provedena v souladu s návodem k použití.

Záruční lhůta: 12 měsíců

Při platbě v CZK (nutno uvést v objednávce) bude použit kurz 25,43

CZK/EUR platný do 31.10.2018.

Upozorňujeme, že tato nabídka obsahuje informace spadající do obchodního tajemství firmy Pfeiffer Vacuum Austria GmbH a nesmí být zveřejněna, a to ani v Registru smluv coby součást objednávky. Pro účely zveřejnění dle zákona č.340/2015 Sb. rádi poskytneme redigovanou nabídku neobsahující citlivé informace.

Doufáme, že nabídka odpovídá Vaším požadavkům a jsme připraveni poskytnout další doplňující informace.

Za zboží	12.016,91
Daňový základ	12.016,91
DPH 0,0%	0,00
Celkem k platbě	12.016,91

Pfeiffer Vacuum Austria GmbH

Nabídka 11 18001940 - 16.10.2018

Pol.	Produkt	Množství	Cena v EUR	
			za MJ	Celkem

Dodací podmínky: FCA

Doprava: Kamion/Spedice

Váha - Netto: 76,154

Platba: 30 dní po vystavení, netto

Bankovní spojení:

Swift/BIC:

Kód banky:

Číslo účtu:

IBAN:

████████████████████ ████████████████████ ████████████████████ ████████████████████ ████████████████████
████████████████████ ████████████████████ ████████████████████ ████████████████████ ████████████████████

- Anzeige / Advert -

VACUUM SOLUTIONS FROM A SINGLE SOURCE
www.pfeiffer-vacuum.com