

Šobr Václav

From: Martin Moser <moser@mit-laser.cz>
Sent: pondělí 5. listopadu 2018 18:25
To: Šobr Václav
Subject: CENOVÁ NABÍDKA č. 38610

(Pokud se Vám tento e-mail nezobrazuje správně, kontaktujte nás prosím.)

Dobrý den,

děkujeme za poptávku a zasíláme Vám následující nabídku:

Pol.	Množ.	Označení zboží	Cena b. DPH Kč	DPH %	DPH Kč	Celkem vč. DPH Kč
1	1 ks	L2000W-BB-120 <i>Thermopile head; 0.19 - 20µm; aperture diam. 120mm; power range 1W - 2000W; energy range 6J - 6000J; power noise level 50mW; min. energy 6J; max. average power density 700W/cm2 at 100W, 60W/cm2 at 2000W; max. energy density 4000J/cm2 for 1s pulses, 30J/cm2 for 10ms pulses, 0.3J/cm2 for < 100ns pulses; response time with display 6s (0-95%, typ.); broad band absorber; water cooled; smart head connector [Ophir / Spiricon]</i>	92 900,00	21	19 509,00	112 409,00
2	1 ks	L250W <i>Thermopile head; 0.19 - 20µm; 4W - 250W, 200mJ - 200J; max. power density 10kW/cm2 at 250W, 14kW/cm2 at 100W; minimum energy 200mJ; power noise level 200mW; aperture diam. 50mm; cw, average power and single pulse measurements (not faster than 1 pulse every 5 seconds); very thin design, 20mm thick; water cooled; smart head [Ophir / Spiricon]</i>	31 500,00	21	6 615,00	38 115,00
3	1 ks	L50(300)A-PF-65 <i>Thermopile head; 0.15 - 20µm; for large beam short pulsed lasers; power range 400mW - 50W cw (150W for 4.5min., 300W for 2min.); power noise level 20mW; max. average power density 3kW/cm2; max. energy density 3J/cm2 for < 100ns single pulses, 1.5J/cm2 for < 100ns pulses, 10 - 50Hz, 40J/cm2 for 10ms pulses; min. energy 200mJ; response time 3s (0-95%); aperture diam. 65mm; PF type absorber; convection/ballistic cooling; smart head connector [Ophir / Spiricon]</i>	28 900,00	21	6 069,00	34 969,00
4	1 ks	30A-P-17 <i>Thermopile head; 150nm - 8µm; volume absorber (P type); cw and short pulse average power; 60mW - 30W cw, 40mJ - 30J pulsed; max. energy density single shot 10J/cm2, 10 - 30Hz 1J/cm2; max. power density 50W/cm2; aperture diam. 17mm; convection cooling; smart head connector [Ophir / Spiricon]</i>	26 100,00	21	5 481,00	31 581,00
5	1 ks	PD300-3W (Version V1) <i>Photo diode head; 350 - 1100nm (without filter), 430 - 1100nm (with filter) (Si-photodiode); cw power measurement; 5nW - 100mW (without filter), 200µW - 3W (with filter) (max. power wavelength dependant); aperture 10x10mm; accuracy ±3% (400-950nm, without filter); damage threshold 10W/cm2 (without filter), 100W/cm2 (with filter); max. pulse energy 20µJ (without filter), 500µJ (with filter); response time</i>	20 900,00	21	4 389,00	25 289,00

		0.2s; automatic background subtraction; incl. attenuation filter (100x); smart head [Ophir / Spiricon]				
6	1 ks	PD300-1W Photo diode head; 350 - 1100nm (without filter), 430 - 1100nm (with filter) (Si-photodiode); cw power measurement; 500pW - 30mW (without filter), 200μW - 1W (with filter) (max. power wavelength dependent); aperture 10x10mm; accuracy ±3% (400-950nm, without filter); damage threshold 10W/cm2 (without filter), 50W/cm2 (with filter); response time 0.2s; automatic background subtraction; incl. attenuation filter; smart head [Ophir / Spiricon]	18 000,00	21	3 780,00	21 780,00
7	1 ks	PE10-C Pyroelectric head; 150nm - 12μm; pulse energy measurement; 1μJ - 10mJ; active aperture diam. 12mm; lowest measurable energy 1μJ; max. pulse width 1μs/30μs (switchable); max. pulse rep. rate 25kHz (max. pulse width setting 1μs), 5kHz (max. pulse width setting 30μs); damage threshold 0.1J/cm2 (< 100ns puls), 3J/cm2 (300μs puls); metallic absorber; smart head; fully compatible with ; needs adapter to be used with Nova or Orion [Ophir / Spiricon]	28 800,00	21	6 048,00	34 848,00
8	1 ks	PE25-C Pyroelectric head; 150nm - 3μm; pulse energy measurement; 8μJ - 10J; active aperture diam. 24.5mm; lowest measurable energy 8μJ (pulse width setting 2μs), 100μJ (pulse width setting 5ms); max. pulse width 5ms/1ms/500μs/30μs/2μs (switchable); max. pulse rep. rate 10kHz to 100Hz (depending on pulse width setting); damage threshold 0.1J/cm2 (< 100ns puls), 6J/cm2 (2ms puls); metallic absorber; smart head; needs adapter to be used with Nova or Orion [Ophir / Spiricon]	27 900,00	21	5 859,00	33 759,00
9	1 ks	PE50-C Pyroelectric head; 150nm - 3μm; pulse energy measurement; 10μJ - 10J; active aperture diam. 46mm; lowest measurable energy 10μJ (pulse width setting 2μs), 100μJ (pulse width setting 5ms); max. pulse width 5ms/1ms/500μs/30μs/2μs (switchable); max. pulse rep. rate 10kHz to 100Hz (depending on pulse width setting); damage threshold 0.1J/cm2 (< 100ns puls), 6J/cm2 (2ms puls); metallic absorber; smart head; needs adapter to be used with Nova or Orion [Ophir / Spiricon]	38 700,00	21	8 127,00	46 827,00
10	1 ks	VEGA Power/energy display; color graphical LCD-display (TFT 320 x 240 pixels); compatible with all Ophir thermopile, pyroelectric and photodiode heads; full wavelength correction; choice of digital or analog needle display; log every pulse at up to 4000Hz with pyro heads; non-volatile on-board storage of up to 50.000 data points in up to 10 files (up to 200.000 data points after firmware upgrade available in 2009); built in RS232 and USB interface; analog output; incl. LabView VIs, Windows COM Object, ActiveX controls (for Visual Basic, C++, etc.), StarLab (StarCom) application software for Windows; [Ophir / Spiricon]	37 600,00	21	7 896,00	45 496,00
11	1 ks	Pulsar-1 High-speed interface; 1-channel smart head to USB interface; to connect 1 energy or power meter head directly to PC through USB interface; compatible with most Ophir smart heads; up to 25kHz real time data logging to	27 608,00	21	5 797,68	33 405,68

PC; BNC-trigger input; incl. application software for Windows, Windows COM Object, ActiveX controls (for Visual Basic, C++, etc.); incl. 12V wall plug power supply [Ophir / Spiricon]

12	1 ks Pulsar-2	37 500,00	21	7 875,00	45 375,00
----	----------------------	-----------	----	----------	-----------

High-speed interface; 2-channel smart head to USB interface; to connect 2 energy and/or power meter heads directly to PC through USB interface; compatible with most Ophir smart heads; up to 25kHz real time data logging to PC; BNC-trigger input; incl. application software for Windows, Windows COM Object, ActiveX controls (for Visual Basic, C++, etc.); incl. 12V wall plug power supply [Ophir / Spiricon]

13	1 ks Pulsar-4	70 900,00	21	14 889,00	85 789,00
----	----------------------	-----------	----	-----------	-----------

High-speed interface; 4-channel smart head to USB interface; to connect up to 4 energy and/or power meter heads directly to PC through USB interface; compatible with most Ophir smart heads; up to 25kHz real time data logging to PC (for heads supporting that rate); BNC-trigger input; incl. application software for Windows, Windows COM Object, ActiveX controls (for Visual Basic, C++, etc.); incl. 12V wall plug power supply [Ophir / Spiricon]

Doprava:

14	1 DAP	1 500,00	21	315,00	1 815,00
----	--------------	----------	----	--------	----------

Dopravné a balné

Dodací doba: cca 5-7 týdnů

Tato nabídka platí: 14 dnů

V ceně je zahrnut recyklační poplatek WEEE.

Firma MIT s.r.o. dodává zboží pouze na základě Všeobecných podmínek prodeje a dodání.

Pozn.:

- Ceny obsahují speciální slevu pro ELI Beamlines.

S pozdravem

Martin Moser

MIT s.r.o.

Lasery, fotonika a jemná mechanika

Klánova 56, CZ - 147 00 Praha 4

Tel.: +420 241 712 548, mob.: +420 777 708 930

moser@mit-laser.com, www.mit-laser.com